

COMPRESSION "F" - PROEasyF "QUICK F" COAXIAL CABLE LEAD




HIGH SHIELDING, CLASS A++ AND LOW ATTENUATION

REF.	ART. NR	DESCRIPTION	EAN 13
3853	FS-FSW2015	CABLE LEAD COMPRESSION "F" - PROEasyF "QUICK F" WHITE 1.5m	4031136022198
385301	FS-FSW2030	CABLE LEAD COMPRESSION "F" - PROEasyF "QUICK F" WHITE 3m	4031136022204
385302	FS-FSW2050	CABLE LEAD COMPRESSION "F" - PROEasyF "QUICK F" WHITE 5m	4031136022211



A cable lead pre-terminated with compression "F" connector at one end (ref. 3802) and PROEasyF "Quick F" at the other end (ref. 413410), and made with a trishield Class A++ coaxial cable: the SK2000+ (ref. 4138xx).



REF.	ART. NR.	 m	 Grs	 Pack u.
3853	FS-FSW2015	1.5	139	30
385301	FS-FSW2030	3	229	20
385302	FS-FSW2050	5	309	15



Ref. / Art.Nr.	3853xx / FS-FSW20xx		
Cable type	Class A++		
Inner conductor	∅	mm	1.02
	Material	-	Cu (copper)
	Resistance	Ohm/Km	22
Dielectric	∅	mm	4.6
	Material	-	PEE (foam polyethylene)
	Over lapped foil	Material	-
Braid	Material	-	CuSn (tinned copper)
	Resistance	Ohm/Km	10.5
	Coverage	%	82
2nd shielding film	-		Yes
Outer sheath	∅	mm	6.7
	Material	-	PVC (polyvinyle clorhidre)
Minimum bending radius	mm		33,5
Shielding at 1GHz	dB		>105 (typ. 130)
Capacitance	pF/m		54
Impedance	Ohm		75
Velocity ratio	%		84
Attenuations dB/m			
Frequency (MHz)	200		0.09
	500		0.14
	800		0.18
	1000		0.21
	1350		0.25
	1750		0.28
	2050		0.31
2300		0.32	