



## Optiks fiber-patchkabel För inomhusbruk LSFH SC/APC, Single-mode (SM)

Single-mode (SM) optisk fiber-patchkabel med SC/APC-kontakter för anslutning av fiberutrustning. Är av LSFH-typ vilket rekommenderas för inomhusbruk. Levereras i plastpåse.

Ref.	232621
	OSK2SCAPC
EAN13	8424450187029

### Andra funktioner

Färg	Orange
Längd	2,00 m

### Förpackning

Påse	1 st.
Låda	10 st.

### Fysisk data

Nettovikt	24,00 g
Bruttovolym	0,27 dm <sup>3</sup>
Bruttovikt	24,00 g
Bredd	3,00 mm
Höjd	2.000,00 mm
Djup	3,00 mm
Huvudproduktens vikt	24,00 g

### Utmärkande egenskaper

- Fiber typ ITU-T G.657.A2
- Med aramid fiber för att stärka strukturen
- Färg: orange, LSFH mantel

- SC/APC-kontakter
- Finns i flera färdigkontakterade längder

## Tekniska specifikationer : Ref. 232621

Fiber core type		Single-mode (ITU-T-G.657.A2)
Optical fiber type category		OS1
Fiber core diameter	µm	9
Fiber cladding diameter	µm	125
Coating buffer diameter	µm	250
Cable structure		Tight buffer
Plastic buffer diameter	mm	0,9
Outer sheath Diameter	mm	3
Outer sheath Material		LSFH
Blocking jelly		No
Attenuation 1310nm	dB/km	< 0,4
Attenuation 1490nm	dB/km	< 0,4
Attenuation 1550nm	dB/km	< 0,3
Insertion losses in connector 2	dB	< 0,5
Return losses in connector 2	dB	> 60
Optical connector type 1		SC
Polishing type (Optical connector 1)		APC
Optical connector type 2		SC
Polishing type (Optical connector 2)		APC
Cable length	m	2
Structure reinforcement element		Aramid fibers
Minimum bending radius	mm	15
Operating temperature	°C	-20 ... 70