



CXT 18VRtC coaxial cable Eca Euroclass

RG-6 coaxial cable with copper inner conductor and copper-clad aluminium braid (Cu/CCA), and double shielded. An 18VRtC cable with PVC sheath.

Ref.	2139
Logical ref.	KE1048B
EAN13	8424450101278

Other features

Colour	Black
Length	100.00 m

Packing

Reel	100 m
Box	500 m
Pallet	6000 m

Physical data

Net weight	50.00 g
Gross weight	50.00 g
Width	6.00 mm
Height	1,000.00 mm
Depth	6.00 mm
Main product weight	41.00 g

Highlights

- Copper inner conductor and copper-clad aluminium braid
- Eca Euroclass

Main features

- White-colour external PVC sheath
- 75 Ohm characteristic impedance
- Available in reels of different lengths

Discover

Double-shielded Class B coaxial cable

They provide two shielding layers and belong in EN 50117 standard Class B, according to their structural properties:

- For 5 MHz - 30 MHz => $TI < 15 \text{ m}\Omega/\text{m}$
- For 30 MHz - 1000 MHz => $SA > 75 \text{ dB}$
- For 1000 MHz - 2000 MHz => $SA > 65 \text{ dB}$
- For 2000 MHz - 3000 MHz => $SA > 55 \text{ dB}$

Where the transfer impedance (TI) defines how effective the shielding is at low frequencies, while the shielding attenuation (SA) defines it in the 30 MHz-to-3000 MHz range.

Double-shielded Class B coaxial cable

They provide two shielding layers and belong in EN 50117 standard Class B, according to their structural properties:

- For 5 MHz - 30 MHz => $TI < 15 \text{ m}\Omega/\text{m}$
- For 5 MHz - 1000 MHz => $SA > 75 \text{ dB}$
- For 1000 MHz - 2000 MHz => $SA > 65 \text{ dB}$
- For 2000 MHz - 3000 MHz => $SA > 55 \text{ dB}$

Where the transfer impedance (TI) defines how effective the shielding is at low frequencies, while the shielding attenuation (SA) defines it in the 30 MHz-to-3000 MHz range.

Mounting details

DETAIL VIEW OF THE COAXIAL CABLE SECTION

A-Inner conductor

B-Dielectric

C-Foil

D-Braid

E-Outer sheath



