

Class A+ coaxial cable lead, trishielded, without connectors

RG-6 coaxial cable without connectors, made of copper-clad steel inner conductor and aluminium braid (CCS/Al), with an outstanding braid coverage (60%). Triple shielded (TSH) cable, equipped with a second foil for extra shielded.

Suitable for professional use, besides the regular use in the connection between outlet and TV devices.

Ref.	4371
EAN13	8424450043714

Other features	
Colour	White
Length	10.00 m

Physical data	
Net weight	400.00 g
Gross volume	2.50 dm³
Gross weight	400.00 g
Width	140.00 mm
Height	59.00 mm
Depth	140.00 mm

Packaging info	
Blister	1 pcs.
Box	10 pcs.
Bucket	20 pcs.

Highlights

- Copper-clad steel inner conductor and aluminium braid
- Triple shielded, class A+. Eca Euroclass
- White-colour external PVC sheath, for indoor use
- Available in different lengths

Discover

Class A++ Trishield (TSH) coaxial cable

With three shielding layers (Trishield), this cables provide the highest immunity to interference thanks to its very high shielding. Recommended in cases of high electromagnetic noise levels.

They belong in EN 50117 standard Class A++, according to their structural properties:

- For 5 MHz - 30 MHz => TI < 0.9 mΩ/m
- For 30 MHz - 1000 MHz => SA > 105 dB
- For 1000 MHz - 2000 MHz => SA > 95 dB
- For 2000 MHz - 3000 MHz => SA > 85 dB

Where the transfer impedance (TI) defines how effective the shielding is at low frequencies, while the shielding attenuation (SA) defines it in the 30 MHz-to-3000 MHz range.

Televes®

Technical specifications : Ref. 4371

Model		SK6Fplus
Cable type		RG-6
Standard		EN 50117-2-4
Euroclass		Eca
Class		A+
Inner conductor Diameter	in	0.04
Inner conductor Material		Copper-clad steel (CCS)
Inner conductor Resistance	Ohm/km	< 110
Dielectric Diameter	in	0.181
Dielectric Material		Foam polyethylene (PEE)
Dielectric Color		White RAL 9003
Overlapped foil		Aluminium + Polyester
Braid Material		Aluminium
Braid dimensions: No. of carriers (Nc)		16
Braid Dimensions: No. of strands per carrier (Ns)		6
Braid Dimensions: strand diameter (Ø)	in	0.005
Braid Resistance	Ohm/km	< 30
Braid Coverage	%	60
2nd foil		Yes
2nd foil glued to the dielectric		No
Petrol-Jelly		No
Anti-migrating film		No
Outer sheath Diameter	in	0.268
Outer sheath Material		PVC
Outer sheath Thickness	in	0.012
Minimum bending radius	in	1.339
Transfer impedance (5-30MHz)	mΩ /m	< 2.5
1GHz shielding	dB	> 95
Spark Test	Vac	3000
Capacitance	pF/m	53
Impedance	Ω	75
Velocity ratio	%	82
Operating temperature	°F	-22 ... 158
Atenuacion 5MHz	dB/m	0.02
Atenuacion 47MHz	dB/m	0.05
Atenuacion 54MHz	dB/m	0.05
Atenuacion 90MHz	dB/m	0.06
Atenuacion 200MHz	dB/m	0.1
Atenuacion 500MHz	dB/m	0.15
Atenuacion 698MHz	dB/m	0.17
Atenuacion 800MHz	dB/m	0.19
Atenuacion 862MHz	dB/m	0.2
Atenuacion 950MHz	dB/m	0.2
Atenuacion 1000MHz	dB/m	0.22
Atenuacion 1220MHz	dB/m	0.22
Atenuacion 1350MHz	dB/m	0.25
Atenuacion 1750MHz	dB/m	0.29
Atenuacion 2050MHz	dB/m	0.31
Atenuacion 2150MHz	dB/m	0.31
Atenuacion 2200MHz	dB/m	0.32
Atenuacion 2300MHz	dB/m	0.33
Atenuacion 2400MHz	dB/m	0.34
Atenuacion 3000MHz	dB/m	0.4