



End Outlet 2 connectors: FM-TV

End outlet equipped with two IEC connectors. The left connector is a male IEC for terrestrial TV, the right connector is a female IEC for radio (FM).

Ref.	5230
EAN13	8424450052303

Other features

Complement	Outlet
-------------------	--------

Packaging info

Box	1 pcs.
Carton	10 pcs.
Pallet	3600 pcs.

Physical data

Net weight	90.00 g
Gross volume	0.20 dm ³
Gross weight	90.00 g
Width	70.00 mm
Height	70.00 mm
Depth	27.00 mm
Main product weight	90.00 g

Highlights

- Robot-controlled automated manufacturing
- High shielding
- Outstanding isolation between outputs
- Made of Zamak, high strength

- Compatible with coaxial cable with sheath diameters in the 5-to-6,9 mm range (Ø 5...6,9 mm)

Discover

Televes outlets: Screw-free mounting

A class A outlet offering numerous advantages:

- The inner conductor is connected simply by pushing, without the need for screws; still the gripping force is equivalent
- Supports inner conductor diameters from 0.65 mm to 1.2 mm, and external cable diameters from 5 mm to 6.9 mm
- F-connector type conic guide for easy inner conductor introduction
- Wide margin in inner conductor length (from 5 mm to 15 mm), which makes short circuits between core and mesh difficult
- Tilt-up, self-supporting, full-opening clamp
- The clamp is equipped with 3 jagged rows in 9 mm for a perfect braid fixing
- Printed circuit board perforation to make the faceplate fixing screw compatible
- Rounded edges to prevent cuts
- Class A shielding

Furthermore, this product range includes several engravings on the chassis:

- CE marking
- Numerical and logical references
- Input and output indications
- Cable stripping dimensions

Technical specifications : Ref. 5230

Fastening method			Without screws	
Number of connectors			2	
R Connector			"IEC" female	
TV Connector			"IEC" male	
Pass-through output			No	
Bands				
Frequency range	MHz	FM		TV
		87.5 ... 108		5 ... 862
Attenuation: R Connector	dB	18		--
Attenuation: TV Connector	dB	--		4,5