
End Outlet Diplexed 2 connectors: FM/TV-SAT



End outlet diplexed equipped with two IEC connectors. The left connector is a male IEC for FM (radio), while the right connector is a female IEC for satellite TV (SAT).

Ref.	5276
EAN13	8424450122853

Other features	
Complement	Outlet
Outlet design	Without clamps

Physical data	
Net weight	90.00 g
Gross volume	0.20 dm³
Gross weight	90.00 g
Width	70.00 mm
Height	70.00 mm
Depth	27.00 mm
Main product weight	83.00 g

Packaging info	
Box	1 pcs.
Carton	10 pcs.
Carton	100 pcs.
Pallet	3000 pcs.

Highlights

- High-rejection separation filter: the SAT signal is filtered in the FM/TV IEC male connector , while the terrestrial FM/TV signal is filtered in the satellite IEC female connector.
- Robot-controlled automated manufacturing
- High shielding
- Outstanding isolation between outputs
- Made of Zamak, high strength

- DC pass from the SAT connector to the input
- Compatible with coaxial cable with sheath diameters in the 5-to-6,9 mm range (Ø 5...6,9 mm)

Discover

Televes outlets: Screw-free mounting

A class A outlet offering numerous advantages:

- The inner conductor is connected simply by pushing, without the need for screws; still the gripping force is equivalent
- Supports inner conductor diameters from 0.65 mm to 1.2 mm, and external cable diameters from 5 mm to 6.9 mm
- F-connector type conic guide for easy inner conductor introduction
- Wide margin in inner conductor length (from 5 mm to 15 mm), which makes short circuits between core and mesh difficult
- Tilt-up, self-supporting, full-opening clamp
- The clamp is equipped with 3 jagged rows in 9 mm for a perfect braid fixing
- Printed circuit board perforation to make the faceplate fixing screw compatible
- Rounded edges to prevent cuts
- Class A shielding

Furthermore, this product range includes several engravings on the chassis:

- CE marking
- Numerical and logical references
- Input and output indications
- Cable stripping dimensions

Technical specifications : Ref. 5276

Fastening method		Without screws	
Number of connectors		2	
R/TV Connector		"IEC" male	
SAT Connector		"IEC" female	
Pass-through output		No	
Bands		TV	SAT
Frequency range	MHz	5 ... 862	950 ... 2400
Rejection between outputs	dB	> 10	> 15
Attenuation: R/TV Connector	dB	1	--
Attenuation: SAT Connector	dB	--	1.5
DC pass		SAT In	
Max. current	mA	350	