


Ellipse Antenna UHF, 2nd Digital Dividend (LTE700)

Intelligence taken to the limit

Ellipse is an intelligent antenna that adapts automatically and in real time to the conditions signals are received. It has been designed to offer a stable and quality reception of DTT (UHF) signals, optimizing the rejection of the LTE band (up to channel 48) thanks to a SAW filter that offers great selectivity.
A new concept of DTT antenna that eliminates any interference even in the limits of the TV band, combining a break-through design in a 100% stainless mechanical frame that houses the new generation of Tforce electronics, featuring a revolutionary SAW filter.

RED compliant.

PSU included: intelligence is activated when the antenna is powered (according to reference).

Ref.	148923
EAN13	8424450201831

Other features	
Colour	Orange
Power Supply Unit	12V, UK plug
Supply method	Single packing

Packaging info	
Box	1 pcs.
Carton	4 pcs.

Physical data	
Net weight	1,800.00 g
Gross volume	39.40 dm³
Gross weight	2,400.00 g
Width	860.00 mm
Height	685.00 mm
Depth	555.00 mm
Main product weight	1,500.00 g

Highlights

- The best antenna for range of DTT coverage: It receives the signal in multiple locations, whether the signal is strong or weak
- The highest dynamic range: it allows the reception of a quality signal in a variety of situations, detecting very weak signals and avoiding overload with overly strong signals
- Capable of adapting to adverse weather conditions, locations with a "fading" effect or to any change in the environment: it is constantly checking the signal and autoadjusting its gain in order to always provide the best output level possible
- Optimal C/N: the signal quality is always preserved thanks to a very low noise figure
- Optimal gain: intelligence autoadjusts the gain to the optimal level
- Eliminate any interference, even in the limits of the TV band: thank to its SAW filter (Surface Acoustic Wave), which performs a great selectivity, interferences are filtered, mainly the telephone LTE ones, respecting the last channel of the band
- Special double-U dipole: it's open/close format provides optimal frequency response flatness
- A fully shielded switch box protects the BOSS system from impulsive noise; grounded for full protection against electrical discharge
- Mechanics completely immune to corrosion: Aluminium and fiberglass structure, stainless steel screws and reinforced ZAMAK clamp with an anticorrosive core
- Innovative aerodynamic design: Unsurpassed aesthetics show a meticulous design and passion for details
- Curves enhance reception: the concave surface created by the reflectors focus the signal on the dipole. The convex external side maximize screening and rejection against interference
- Assembly process: Quick assembly in less than 30 seconds and all the installation is carried out with no tools required
- A robust and permanent fastening system that avoids malfunctioning over time
- Extremely lightweight and compact: it makes installation in challenging locations easier and offers lower wind resistance
- Low consumption in intelligent mode
- Made in Europe: Manufactured in a fully automated production and verification line that ensures the highest level of performance guarantee

Discover


TForce technology:

Televes transitions from the traditional silicon era into a new era of electronic component design, allowing integrated circuits to be precisely manufactured for microwave frequency bands. Utilizing “State of the Art” MMIC technology TForce is manufactured using semiconductor compounds such as gallium arsenide (GaAs), providing the resulting products with unparalleled features and performance


Televes has reinvented the antenna concept. Until now, an antenna was just the reception component of a TV installation in which gain and directivity were the main features. The introduction of a smart device like BOSS provides the antenna with the capacity to receive very weak signals without the risk of being affected by very strong signals, the result is a dynamic balance between weak and strong signals that provides optimum signal levels at all times: the "dynamic range" concept turns out to be the most outstanding among quality parameters.

The creation of TForce with BOSS technology using MMIC components is an extraordinary milestone in the optimization of the dynamic range. The technology that allowed the reception of lost signals from distant satellites is now allowing the enhancement of the coverage range in DTT installations.


Application example



Graphic documentation



Frequency response



Radiation pattern

Televes®

Technical specifications : Ref. 148923

Bands		UHF
Frequency range	MHz	470 ... 694
Channels		21 ... 48
BOSS mode		ON
Gain	dBi	40
Output level		Auto*[1]
Noise figure	dB	2.5
Signal level of use	dB	< 15
Max. current	mA	40
Beamwidth	°	30
F/B ratio	dB	> 20
Wind load (@80miles/h)	N	96
Wind load (@93miles/h)	N	132
Mast diameter	in	0.787 ... 1.969

*[1] The gain is automatically adjusted according to the level of output.