



## Ethernet Patch Cord U/UTP Cat 6 PVC, white

Preconnected Ethernet patch cord with RJ45 connector at each end. It is made of a Category-6 data cable, U/UTP type, with a flexible copper inner conductor 24 AWG and outer sheath made of white PVC.

<b>Ref.</b>	209016
<b>Logical ref.</b>	PK6P7W
<b>EAN13</b>	8424450222027

### Other features

<b>Colour</b>	White
<b>Length</b>	7.00 m

### Packaging info

<b>Box</b>	10 pcs.
------------	---------

### Physical data

<b>Net weight</b>	263.00 g
<b>Gross volume</b>	0.09 dm <sup>3</sup>
<b>Gross weight</b>	263.00 g
<b>Width</b>	12.00 mm
<b>Height</b>	7,085.00 mm
<b>Depth</b>	10.00 mm

### Highlights

- U/UTP data Cable
- Flexible copper inner conductor (24 AWG)
- Compatible with PoE/PoE+ (Power over Ethernet) technology, allowing the cable to power network devices
- PVC (polyvinyl chloride) outer sheath
- 72% nominal speed

- RJ45 connectors with gold plated connector ends

## Discover

---

### Category 6

Data cable category Cat 6 complies with the standard for Gigabit Ethernet and it is backwards compatible, with the standards of the inferior categories (Cat 5/5e and Cat 3). Category 6 evolves over category 5E, allowing to achieve transmission frequencies of up to 250 MHz (in each pair) and 1 Gbps of throughput. It includes characteristics and specifications to avoid crosstalk and noise. This type of data cable can be used in 10BASE-T, 100BASE-T and 1000BASE-T (Gigabit Ethernet) compliant systems.

Our category 6 cables are characterized:

- Comply with TIA/EIA-568B.2-1
- Crucifix type padding
- Transfer rate up to 1Gbps
- Frequency range of up to 250 MHz and up to 400MHz in some references
- Includes rip cord to make it easier to strip the cable
- Nominal impedance of 100 ohms
- Maximum resistance per conductor below 9.38 ohms/100m

The RJ45 is a connector commonly used in structured cable networks. With up to 8 connection pins, it is adequate both for data networks (8 pairs), as well as telephone networks (2 pairs). It is usually used in networks compliant with standards TIA/EIA-568-B.

### What is the PoE technology?

PoE (Power over Ethernet) technology enables the simultaneous transmission of power and data over the same Ethernet network cable, eliminating the need for separate power supplies. Currently, there are three main standards: IEEE 802.3af (PoE), IEEE 802.3at (PoE+), and IEEE 802.3bt (PoE++/4PPoE).

The latter defines two additional types (Type 3 and Type 4) with higher power levels, making four PoE levels in total.

The three aspects that differentiate the different types of PoE are:

- Maximum PSE (Power Sourcing Equipment) Power: Indicates the maximum amount of electrical power that can be supplied by an equipment over the Ethernet cable.
- Power for the PD (Powered Device): This is the electrical power that can be received by the device powered by the cable.
- Number of Twisted Pairs Used: Refers to how many twisted pairs in the Ethernet cable are used to deliver electrical power.

Standard	Type of PoE		Maximum PSE Power	Power for the PD	No. of Pairs Used
<b>IEEE 802.3af</b>	Type 1	PoE	15.4W	12.95W	2
<b>IEEE 802.3at</b>	Type 2	PoE+	30W	25.5W	2
<b>IEEE 802.3bt</b>	Type 3	PoE++	60W	51W	4
	Type 4	4PPoE	90-100W	71W	4

Recommended uses according to PoE type:

- Type 1: IP phones, basic IP cameras, low-demand Wi-Fi access points, sensors or simple IoT devices.
- Type 2: Dual band Wi-Fi access points, IP motion cameras (PTZ), IP video phones, alarm systems.
- Type 3: Wi-Fi 6 / Wi-Fi 6E access points, heated PTZ cameras, multimedia terminals, video conferencing equipment.
- Type 4: Monitors or touch screens, desktops, high-performance network equipment.

Devices compatible with a specific type of PoE can also be powered using a higher type, which provides greater versatility and scalability in installations.

The recommended data cables and connectors for Types 3 and 4 are CAT6A and above with shielding. This recommendation is based on their better ability to dissipate the heat generated during the transmission of electrical power.

CAT6A UTP cables and connectors are technically compatible with PoE++ technology, but they may present limitations over distances greater than 55 m. Since they lack shielding, thermal dissipation is less efficient, which can cause voltage drops along the run and affect the proper operation of the powered device. This also happens with CAT5e and CAT6; they are compatible with PoE++ but not recommended for distances over 55 m.

Main advantages of PoE technology in installations:

- Quick and cost-effective installation by using the same cable for power and data transmission.

- Greater installation flexibility as there is no need to rely on auxiliary power sockets.
- More efficient management and optimised maintenance thanks to the monitoring and administration of the power supply of all equipment from a single point.
- Cost reduction by avoiding electrical conduits and external power supplies.
- Increased safety by minimising electrical risks in the installation, thanks to the use of low voltage.

## Technical specifications : Ref. 209016

Type																				U/UTP
Categorie																				Cat 6
Transmission bandwidth																				250MHz
Transfer rate																				1Gbps
Conductor Diameter		in																		0.007
Conductor Material																				Flexible copper
Conductor type AWG																				24
Conductor isolation Diameter		in																		0.038
Conductor isolation Material																				Polyethylene
Crucifix filler																				Yes
Outer sheath Diameter		in																		0.224
Outer sheath Material																				PVC
Outer sheath Thickness		in																		0.024
Rip cord																				No
Cable length		m																		7
Data connector type																				RJ45
Spark Test		Vac																		3000
Nominal impedance		$\Omega$																		100
Conductor resistance		Ohm/km																		< 117
Nominal speed		%																		72
Working voltage		V																		300
Operating temperature		$^{\circ}\text{F}$																		-22 ... 158
Frequencies			1 MHz	4 MHz	8 MHz	10 MHz	16 MHz	20 MHz	25 MHz	31,25 MHz	62,5 MHz	100 MHz	200 MHz	250 MHz						
NEXT (typ.)	dB/100m		65	63	58.2	56.6	53.2	51.6	50	48.4	43.4	39.9	34.8	33.1						
PS NEXT (typ.)	dB/100m		62	60.5	55.6	54	50.6	49	47.3	45.7	40.6	37.1	31.9	30.2						
ACR-F (typ.)	dB/100m		63.3	51.2	45.2	43.3	39.2	37.2	35.3	33.4	27.3	23.3	17.2	15.3						
PS ACR-F (typ.)	dB/100m		60.3	48.2	42.2	40.3	36.2	34.2	32.3	30.4	24.3	20.3	14.2	12.3						
Return losses	dB		19	19	19	19	18	17.5	17	16.5	14	12	9	8						