



Ethernet Patch Cord S/FTP Cat 6A LSFH, grey

Preconnected Ethernet patch cord with RJ45 connector at each end. It is made of a Category-6A data cable, S/FTP type (foiled pairs and foiled cable), with a flexible copper inner conductor 26 AWG and outer sheath made of grey LSFH (Low Smoke Free of Halogen).

Ref.	209113
Logical ref.	PK6AL2G
EAN13	8424450250853

Other features

Colour	Grey
Length	2.00 m

Packaging info

Box	10 pcs.
------------	---------

Physical data

Net weight	68.00 g
Gross volume	0.45 dm ³
Gross weight	68.00 g
Width	12.00 mm
Height	2,025.00 mm
Depth	10.00 mm
Main product weight	79.00 g

Highlights

- S/FTP data Cable
- Flexible copper inner conductor (26 AWG)
- Compatible with PoE/PoE+ (Power over Ethernet) technology, allowing the cable to power network devices

- Aluminium+polyester shielding foil
- Aluminium outer shielding braid
- LSFH (Low Smoke Free Of Halogen) outer sheath
- 79% nominal speed
- RJ45 connectors with gold plated connector ends with shell nickel plated

Discover

Category 6A

Data cable category Cat 6A (augmented) has its origins on Cat 6 and it is backwards compatible, with the standards of the inferior categories (Cat 6/5e and Cat 3). Category 6A evolves over category 6, allowing to achieve transmission frequencies of up to 500 MHz (in each pair) and 10 Gbps of throughput. It includes characteristics and specifications to avoid crosstalk and noise. This type of data cable can be used in 10BASE-T, 100BASE-T, 1000BASE-T and 10GBASE-T compliant systems.

Our category 6A cables are characterized for:

- Comply with TIA/EIA-568B.2-1
- Transfer rate up to 10Gbps
- Frequency range of up to 650 MHz (higher than the 500 MHz specified by the standard)
- Nominal impedance of 100 ohms
- Maximum resistance per conductor below 9.38 ohms/100m

The RJ45 is a connector commonly used in structured cable networks. With up to 8 connection pins, it is adequate both for data networks (8 pairs), as well as telephone networks (2 pairs). It is usually used in networks compliant with standards TIA/EIA-568-B.

What is the PoE technology?

PoE (Power over Ethernet) technology enables the simultaneous transmission of power and data over the same Ethernet network cable, eliminating the need for separate power supplies. Currently, there are three main standards: IEEE 802.3af (PoE), IEEE 802.3at (PoE+), and IEEE 802.3bt (PoE++/4PPoE). The latter defines two additional types (Type 3 and Type 4) with higher power levels, making four PoE levels in total.

The three aspects that differentiate the different types of PoE are:

- Maximum PSE (Power Sourcing Equipment) Power: Indicates the maximum amount of electrical power that can be supplied by an equipment over the Ethernet cable.
- Power for the PD (Powered Device): This is the electrical power that can be received by the device powered by the cable.
- Number of Twisted Pairs Used: Refers to how many twisted pairs in the Ethernet cable are used to deliver electrical power.

Standard	Type of PoE		Maximum PSE Power	Power for the PD	No. of Pairs Used
IEEE 802.3af	Type 1	PoE	15.4W	12.95W	2
IEEE 802.3at	Type 2	PoE+	30W	25.5W	2
IEEE 802.3bt	Type 3	PoE++	60W	51W	4
	Type 4	4PPoE	90-100W	71W	4

Recommended uses according to PoE type:

- Type 1: IP phones, basic IP cameras, low-demand Wi-Fi access points, sensors or simple IoT devices.
- Type 2: Dual band Wi-Fi access points, IP motion cameras (PTZ), IP video phones, alarm systems.
- Type 3: Wi-Fi 6 / Wi-Fi 6E access points, heated PTZ cameras, multimedia terminals, video conferencing equipment.
- Type 4: Monitors or touch screens, desktops, high-performance network equipment.

Devices compatible with a specific type of PoE can also be powered using a higher type, which provides greater versatility and scalability in installations.

The recommended data cables and connectors for Types 3 and 4 are CAT6A and above with shielding. This recommendation is based on their better ability to dissipate the heat generated during the transmission of electrical power.

CAT6A UTP cables and connectors are technically compatible with PoE++ technology, but they may present limitations over distances greater than 55 m. Since they lack shielding, thermal dissipation is

less efficient, which can cause voltage drops along the run and affect the proper operation of the powered device. This also happens with CAT5e and CAT6; they are compatible with PoE++ but not recommended for distances over 55 m.

Main advantages of PoE technology in installations:

- Quick and cost-effective installation by using the same cable for power and data transmission.
- Greater installation flexibility as there is no need to rely on auxiliary power sockets.
- More efficient management and optimised maintenance thanks to the monitoring and administration of the power supply of all equipment from a single point.
- Cost reduction by avoiding electrical conduits and external power supplies.
- Increased safety by minimising electrical risks in the installation, thanks to the use of low voltage.

Technical specifications : Ref. 209113

Type		S/FTP													
Categorie		Cat 6A													
Transmission bandwidth		650MHz													
Transfer rate		10Gbps													
Conductor Diameter	in	0.006													
Conductor Material		Flexible copper													
Conductor type AWG		26													
Conductor isolation Diameter	in	0.043													
Conductor isolation Material		Polyethylene													
Crucifix filler		No													
Shielding foil of pairs		Aluminium + Polyester													
Outer shielding braid		Aluminium													
Outer sheath Diameter	in	0.244													
Outer sheath Material		LSFH													
Outer sheath Thickness	in	0.023													
Rip cord		No													
Cable length	m	2													
Data connector type		RJ45													
Spark Test	Vac	3000													
Nominal impedance	Ω	100													
Conductor resistance	Ohm/km	< 100													
Nominal speed	%	79													
Working voltage	V	300													
Operating temperature	$^{\circ}$ F	-13 ... 158													
Frequencies		1 MHz	4 MHz	8 MHz	10 MHz	16 MHz	20 MHz	25 MHz	31,25 MHz	62,5 MHz	100 MHz	200 MHz	250 MHz	500 MHz	
NEXT (typ.)	dB/100m	65	63	58.2	56.6	53.2	51.6	50	48.4	43.4	39.9	34.8	33.1	27.9	
PS NEXT (typ.)	dB/100m	62	60.5	55.6	54	50.6	49	47.3	45.7	40.6	37.1	31.9	30.2	24.8	
ACR-F (typ.)	dB/100m	63.3	51.2	45.2	43.3	39.2	37.2	35.3	33.4	27.3	23.3	17.2	15.3	9.3	
PS ACR-F (typ.)	dB/100m	60.3	48.2	42.2	40.3	36.2	34.2	32.3	30.4	24.3	20.3	14.2	12.3	6.3	
Return losses	dB	19	19	19	19	18	17.5	17	16.5	14	12	9	8	6	