



## RJ45 male connector pass through UTP Cat 6 for data cables

RJ45 UTP Cat 6 male pass through connector to connect data cables. The pass-through type system provides convenience and reliability when connecting a cable. The pairs are inserted through all the way to the other end, ensuring that they all reach the bottom of the connector and then the excess is cut off. This ensures that the pairs are in contact with the pins and the connector is accurately connected.

In addition, the probability of error is reduced, as the pass-through design allows for a visual check at the connector output to ensure that the pair order complies with the chosen TIA standard.

Recommended for PoE and PoE+.

<b>Ref.</b>	209906
<b>Logical ref.</b>	CAT6S-U-D
<b>EAN13</b>	8424450267783

### Other features

<b>Supply method</b>	Plastic box (100 units)
----------------------	-------------------------

### Packaging info

### Physical data

<b>Net weight</b>	1.00 g
<b>Gross volume</b>	0.00 dm <sup>3</sup>
<b>Gross weight</b>	1.00 g
<b>Width</b>	11.00 mm

<b>Plastic box</b>	100 pcs.	<b>Height</b>	21.00 mm
		<b>Depth</b>	10.00 mm
		<b>Main product weight</b>	1.00 g

## Highlights

- Lower rejection rate: as the pairs are stuck out of the end of the connector, the excess is cut off, ensuring a correct length and therefore, a reliable connection is always achieved
- Better NEXT levels: by fitting the pairs all the way to the end of the connector, the twist can be kept very close to the pins, reducing the risk of NEXT dropping, as the NEXT decreases as the twist is lost
- Extra security thanks to easy verification that all wires are correctly inserted
- Multiple-connection guaranteed without losses
- Technically compatible with PoE/PoE+/PoE++ (Power over Ethernet) technology, allowing the cable to power network devices
- Compatible with Cat 6 or below
- Mounting requires a crimping tool for pass-through connectors (Ref. 209802)
- 50 microns gold-plated pins

## Discover

### What is the RJ45?

The RJ45 is a connector commonly used in structured cable networks. With up to 8 connection pins, it is adequate both for data networks (8 pairs), as well as telephone networks (2 pairs). It is usually used in networks compliant with standards TIA/EIA-568-B.

## Compatibility of RJ45 connectors with Televes data cables:

Reference	CAT 6							CAT 6A				CAT 7	CAT 7A
	212201	212330	2123	212302	212305	212310	212101	219302	219312	219322	219332	219102	219202
Female connectors	209901/209907	OK	OK	OK	OK	OK	OK	X	X	X	X	X	X
	209905	OK	OK	OK	OK	OK	OK	X	X	X	X	X	X
	209921/209925	OK	OK	OK	OK	OK	OK	X	X	OK	X	OK	X
	209926	OK	OK	OK	OK	OK	OK	X	X	OK	X	OK	X
	209903	OK*	OK*	OK*	OK*	OK*	OK*	OK	X	X	X	X	X
	209923	OK*	OK*	OK*	OK*	OK*	OK*	OK	OK	OK*	OK	OK*	**
	209929/209501	OK*	OK*	OK*	OK*	OK*	OK*	OK	OK	OK*	OK	OK*	**
Male connectors	209902	OK	OK	OK	OK	OK	OK	X	X	X	X	X	X
	209961/209962	OK	OK	OK	OK	OK	OK	X	X	X	X	X	X
	209904	OK*	OK*	OK*	OK*	OK*	OK*	OK	X	X	X	X	X
	209906	OK	OK	OK	OK	OK	OK	X	X	X	X	X	X
	209965/209966	OK	OK	OK	OK	OK	OK	X	X	X	X	X	X
	209922	OK*	OK*	OK*	OK*	OK*	OK*	X	X	OK	X	OK	X
	209924	OK*	OK*	OK*	OK*	OK*	OK*	OK*	OK	OK*	OK	OK	**

OK Compatible

OK\* Compatible, but there are better choices

X Incompatible

\*\* Mechanical compatibility

## What is the PoE technology?

PoE (Power over Ethernet) technology enables the simultaneous transmission of power and data over the same Ethernet network cable, eliminating the need for separate power supplies. Currently, there are three main standards: IEEE 802.3af (PoE), IEEE 802.3at (PoE+), and IEEE 802.3bt (PoE++/4PPoE).

The latter defines two additional types (Type 3 and Type 4) with higher power levels, making four PoE levels in total.

The three aspects that differentiate the different types of PoE are:

- Maximum PSE (Power Sourcing Equipment) Power: Indicates the maximum amount of electrical power that can be supplied by an equipment over the Ethernet cable.
- Power for the PD (Powered Device): This is the electrical power that can be received by the device powered by the cable.
- Number of Twisted Pairs Used: Refers to how many twisted pairs in the Ethernet cable are used

to deliver electrical power.

Standard	Type of PoE		Maximum PSE Power	Power for the PD	No. of Pairs Used
<b>IEEE 802.3af</b>	Type 1	PoE	15.4W	12.95W	2
<b>IEEE 802.3at</b>	Type 2	PoE+	30W	25.5W	2
<b>IEEE 802.3bt</b>	Type 3	PoE++	60W	51W	4
	Type 4	4PPoE	90-100W	71W	4

Recommended uses according to PoE type:

- Type 1: IP phones, basic IP cameras, low-demand Wi-Fi access points, sensors or simple IoT devices.
- Type 2: Dual band Wi-Fi access points, IP motion cameras (PTZ), IP video phones, alarm systems.
- Type 3: Wi-Fi 6 / Wi-Fi 6E access points, heated PTZ cameras, multimedia terminals, video conferencing equipment.
- Type 4: Monitors or touch screens, desktops, high-performance network equipment.

Devices compatible with a specific type of PoE can also be powered using a higher type, which provides greater versatility and scalability in installations.

The recommended data cables and connectors for Types 3 and 4 are CAT6A and above with shielding. This recommendation is based on their better ability to dissipate the heat generated during the transmission of electrical power.

CAT6A UTP cables and connectors are technically compatible with PoE++ technology, but they may present limitations over distances greater than 55 m. Since they lack shielding, thermal dissipation is less efficient, which can cause voltage drops along the run and affect the proper operation of the powered device. This also happens with CAT5e and CAT6; they are compatible with PoE++ but not recommended for distances over 55 m.

Main advantages of PoE technology in installations:

- Quick and cost-effective installation by using the same cable for power and data transmission.
- Greater installation flexibility as there is no need to rely on auxiliary power sockets.
- More efficient management and optimised maintenance thanks to the monitoring and administration of the power supply of all equipment from a single point.
- Cost reduction by avoiding electrical conduits and external power supplies.
- Increased safety by minimising electrical risks in the installation, thanks to the use of low voltage.

## Technical specifications : Ref. 209906

Data connector model			Male
Data connector type			RJ45
Categorie			Cat 6
Shielding type			UTP
Housing material			Polycarbonate
Voltage max.	Vac		125
Max. current	A		1.5
Contact resistance	mΩ		20
Insulation resistance	MΩ		500
Dielectric strength (60Hz/1min)	Vac		1000
Conductor type AWG			26 ... 23
Special tool required			Yes
Durability (connection cycles)			750
Reusable			No
Cable output			180°