MLL-200 Koaxialkabel (50 Ohm) Eca Euroclass, A class skärmad



Koaxkabel (50 Ohm) med kopparpläterad aluminium i innerledaren och skärm av aluminium braid (CCA/Al), och en utomordentligt tät skärm med 90% täckning. En andra skärm finns i form av folie. Kabeln är UV-resistent och halogenfri (LSFH).

Ref.	215801
	SK50OL
EAN13	8424450197523

Andra funktioner	
Färg	Vit
Längd	150,00 m

Fysisk data	
Nettovikt	28,00 g
Bruttovolym	0,06 dm³
Bruttovikt	28,00 g

Förpackning	
Rulle	150 m
Låda	600 m
Lastpall	7200 m

Utmärkande egenskaper

- Kopparpläterad aluminium i innerledare och skärm av aluminium
- Class A skärmad
- Eca Euroclass
- 100m plastrulle

Tekniska specifikationer : Ref. 215801

Model		MLL-200									
Standard		EN50117-1									
Euroclass		Eca									
Class		A									
Inner conductor Diameter	mm	1,12									
Inner conductor Material		Copper-clad aluminium (CCA)									
Inner conductor Resistance	Ohm/km	< 30									
Dielectric Diameter	mm	2,95									
Dielectric Material		Foam polyethylene (PEE)									
Dielectric Color		White RAL 9003									
Overlapped foil		Aluminium + Polyester									
Braid Material		Aluminium									
Braid dimensions: No. of carriers (Nc)		16									
Braid Dimensions: No. of strands per carrier (Ns)		7									
Braid Dimensions: strand diameter (Ø)	mm	0,12									
Braid Resistance	Ohm/km	< 38									
Braid Coverage	%	90									
Outer sheath Diameter	mm	4,95									
Outer sheath Material		LSFH, UV-resistant									
Outer sheath Thickness	mm	0,7									
Minimum bending radius	mm	25									
Transfer impedance (5-30MHz)	mΩ /m	< 5									
1GHz shielding	dB	> 85									
Spark Test	Vac	2500									
Capacitance	pF/m	80									
Impedance	Ω	50									
Velocity ratio	%	80									
Frequencies		30 MHz	50 MHz	150 MHz	300 MHz	450 MHz	960 MHz	1500 MHz	2000 MHz	2500 MHz	3000 MHz
Attenuation (typ.)	dB/100m	7	8,04	13,11	18,86	23,32	34,81	44,34	51,79	58,54	64,79
Return losses	dB	20	20	20	20	20	20	15	15	15	15