



Pigtail LC/APC, Single-mode (SM), LSFH indoor

Single-mode (SM) pigtail, used for interconnecting optical equipment, have its end pre-terminated with LC/APC connector.

The 900µm cover is of LSFH type and is recommended for indoor use. Additionally, its pre-terminated end has a short boot, facilitating installation in wall sockets, avoiding increases in attenuation due to undesirable bends, allowing the sliding of the patch cord through conduits, reducing the space required for connection, and being less demanding regarding bend radius.

Ref.	230608
Logical ref.	OLCAPCP
EAN13	8424450279434

Other features

Colour	Orange
Supply method	Single packing
Length	1.00 m

Packaging info

Bag	1 pcs.
------------	--------

Physical data

Net weight	2.00 g
Gross volume	0.40 dm ³
Gross weight	3.00 g
Width	1.00 mm
Height	1,000.00 mm
Depth	1.00 mm
Main product weight	2.00 g

Highlights

- ITU-T G.657.A2 fiber type
- LSFH sheath, orange colour
- LC/APC connectors
- 1m long

Technical specifications : Ref. 230608

Fiber core type		Single-mode (ITU-T-G.657.A2)
Fiber core diameter	μm	9
Fiber cladding diameter	μm	125
Coating buffer diameter	μm	250
Cable structure		Tight buffer
Outer sheath Diameter	in	0.035
Outer sheath Material		LSFH
Optical fiber attenuation: 1310nm Max	dB/km	0.4
Optical fiber attenuation: 1550nm Max	dB/km	0.3
Cable length	in	39.37
Insertion losses Max	dB	0.5
Return losses Min	dB	60
Optical connector type		LC
Polishing type (Optical connector)		APC
Operating temperature	°F	-4 ... 158