



## Splitting Terminal Enclosure Up to 12 or 16 fibers

Designed to work as a pass-through and diverting element for optical fiber cables. Commonly used in FTTH projects, inside the buildings (usually in the secondary enclosure).

It has the capacity to house 12 fusions inside it by means of the 2 stowages, of 6 fusions each, pre-installed in the trays. Moreover, thanks to the 2 additional stowages of 8 fusions each, its capacity can be increased to 16 fusions if they are installed in place of the serial ones.

<b>Ref.</b>	231301
<b>Logical ref.</b>	OVB8
<b>EAN13</b>	8424450153222

### Packaging info

<b>Box</b>	1 pcs.
------------	--------

### Physical data

<b>Net weight</b>	730.00 g
<b>Gross volume</b>	3.80 dm <sup>3</sup>
<b>Gross weight</b>	730.00 g
<b>Width</b>	163.00 mm
<b>Height</b>	265.00 mm
<b>Depth</b>	69.00 mm
<b>Main product weight</b>	730.00 g

### Highlights

- Made of plastic
- Multi-fiber cable input/output of the main wiring system made by cones designed to house different fiber diameters
- Equipped with 2 stuffing gland at the bottom for optical fiber output. Each stuffing gland can house 4 cables of two 2 fibers each
- Facilitates the installation of the fusions thanks to its 2 independent and removable trays that can house up to 8 fusions each one
- Allows the number of fibres in the installation to be increased thanks to the 2 additional stowages of 8 fibres each
- Prevents external manipulation thanks to the key lock included in the door
- Protected against solid particles of 1 mm diameter or more and sprayed rain thanks to its IP43 tightness rating
- Extremely high impact protection due to IK10 impact resistance rating
- Including screws for wall mounting
- Dimensions (W x H x D): 163mm x 265mm x 69mm
- Colour grey (RAL 7035)

## Technical specifications : Ref. 231301

Number of fibers			16
Pre-cut openings			No
Independent compartments			No
Closure type			Door
Front door locking system			Key Lock, one-point lock
Type of connections			Fusion splice
Installation type			Wall
Protection index (IP)			43
Protection index (IK)			10
Grounding			No
Material			ABS Plastic
Color			Grey
Height	in		10.433
Width	in		6.417
Depth	in		2.717