



Splitting Terminal Enclosure Up to 12 or 16 fibers

Designed to work as a pass-through and diverting element for optical fiber cables. Commonly used in FTTH projects, inside the buildings (usually in the secondary enclosure).

It has the capacity to house 12 fusions inside it by means of the 2 stowages, of 6 fusions each, pre-installed in the trays. Moreover, thanks to the 2 additional stowages of 8 fusions each, its capacity can be increased to 16 fusions if they are installed in place of the serial ones.

Ref.	231301
Logical ref.	OV8
EAN13	8424450153222

Packaging info

Box	1 pcs.
------------	--------

Physical data

Net weight	730.00 g
Gross volume	3.80 dm ³
Gross weight	730.00 g
Width	163.00 mm
Height	265.00 mm
Depth	69.00 mm
Main product weight	730.00 g

Highlights

- Made of plastic
- Multi-fiber cable input/output of the main wiring system made by cones designed to house different fiber diameters
- Equipped with 2 stuffing gland at the bottom for optical fiber output. Each stuffing gland can house 4 cables of two 2 fibers each
- Facilitates the installation of the fusions thanks to its 2 independent and removable trays that can house up to 8 fusions each one
- Allows the number of fibres in the installation to be increased thanks to the 2 additional stowages of 8 fibres each
- Prevents external manipulation thanks to the key lock included in the door
- Protected against solid particles of 1 mm diameter or more and sprayed rain thanks to its IP43 tightness rating
- Extremely high impact protection due to IK10 impact resistance rating
- Including screws for wall mounting
- Dimensions (W x H x D): 163mm x 265mm x 69mm
- Colour grey (RAL 7035)

Technical specifications : Ref. 231301

Number of fibers		16
Pre-cut openings		No
Independent compartments		No
Closure type		Door
Front door locking system		Key Lock, one-point lock
Type of connections		Fusion splice
Installation type		Wall
Protection index (IP)		43
Protection index (IK)		10
Grounding		No
Material		ABS Plastic
Color		Grey
Height	in	10.433
Width	in	6.417
Depth	in	2.717