



## Splitting Terminal Enclosure Up to 48 fibers

Designed to work as a pass-through and diverting element for optical fiber cables, it can handle up to 48 splices on 4 trays. Commonly used in FTTH projects, inside the buildings (usually in the secondary enclosure).

Its large dimensions make installer's work easier when it comes to merging, splitting and placing the different fibers.

---

<b>Ref.</b>	231302
<b>Logical ref.</b>	OVB24
<b>EAN13</b>	8424450181799

---

### Packaging info

---

<b>Box</b>	1 pcs.
------------	--------

---

### Physical data

---

<b>Net weight</b>	1,371.00 g
<b>Gross weight</b>	1,371.00 g
<b>Width</b>	208.00 mm
<b>Height</b>	291.00 mm
<b>Depth</b>	110.00 mm
<b>Main product weight</b>	1,371.00 g

---

### Highlights

---

- Built in high-resistance ABS
- Fully configurable fiber inputs and outputs
- Fully separable, to facilitate the optical fibers installation/segregation procedure

- Easy to work on, with multiple anchors and fiber guides
- Security: Door with lock, to avoid external manipulation
- Grey colour (RAL 7035)
- Equipped with 8 rubber fiber guides, 4 trays and 8 splice stow supports
- All the accessories required for fiber cable support and wall anchoring are provided
- Ingress protection code IP30 and impact protection code IK10
- Dimensions (W x H x D): 208mm x 291mm x 110mm

## Technical specifications : Ref. 231302

Number of fibers		48
Pre-cut openings		Yes
Independent compartments		No
Closure type		Cover
Front door locking system		Key Lock, one-point lock
Type of connections		Fusion splice
Installation type		Wall
Protection index (IP)		30
Protection index (IK)		10
Grounding		No
Material		ABS Plastic
Colour		Grey
Height	mm	300
Width	mm	206
Depth	mm	110