



Splitting Terminal Enclosure Up to 48 fibers

Designed to work as a pass-through and diverting element for optical fiber cables, it can handle up to 48 splices on 4 trays. Commonly used in FTTH projects, inside the buildings (usually in the secondary enclosure).

Its large dimensions make installer's work easier when it comes to merging, splitting and placing the different fibers.

Ref.	231302
Logical ref.	OVB24
EAN13	8424450181799

Packaging info

Box	1 pcs.
------------	--------

Physical data

Net weight	1,371.00 g
Gross volume	8.00 dm ³
Gross weight	1,371.00 g
Width	208.00 mm
Height	291.00 mm
Depth	110.00 mm
Main product weight	1,371.00 g

Highlights

- Robust material due to ABS plastic construction
- Fully configurable fiber inputs and outputs

- Easy to work on, with multiple anchors and fiber guides
- Equipped with 8 rubber fiber guides, 4 trays and 8 splice stow supports
- Fully separable, to facilitate the optical fibers installation/segregation procedure
- Prevents external manipulation thanks to the key lock included in the door
- Protection against sprayed rain due to IP30 degree of watertightness
- Extremely high impact protection due to IK10 impact resistance rating
- All the accessories required for fiber cable support and wall anchoring are provided
- Dimensions (W x H x D): 208mm x 291mm x 110mm
- Grey colour (RAL 7035)

Technical specifications : Ref. 231302

Number of fibers			48
Pre-cut openings			Yes
Independent compartments			No
Closure type			Cover
Front door locking system			Key Lock, one-point lock
Type of connections			Fusion splice
Installation type			Wall
Protection index (IP)			30
Protection index (IK)			10
Grounding			No
Material			ABS Plastic
Color			Grey
Height	in		11.811
Width	in		8.11
Depth	in		4.331