



Splitting Terminal Enclosure Up to 24 fibers

Designed to work as a pass-through and diverting element for optical fiber cables. It can be used both indoors and outdoors and allows the use of up to 12 SC Simplex or LC Duplex connectors, enabling quick connectorisation, as well as the use of pre-connectorised patch cords.

Can house up to 24 splices.

Ref.	231303
Logical ref.	OVB24A
EAN13	8424450259320

Packaging info

Box	1 pcs.
------------	--------

Physical data

Net weight	1,034.00 g
Gross volume	6.83 dm ³
Gross weight	1,132.00 g
Width	200.00 mm
Height	250.00 mm
Depth	72.00 mm

Highlights

- Robust material due to ABS plastic construction
- Multi-fiber cable input/output of the main wiring system made by cones designed to house different fiber diameters
- Equipped with 2 stuffing gland at the bottom for optical fiber output

- Equipped with 1 removable tray, for easier installation and handling of the fibers
- Includes several areas for fiber confinement, allowing for easy separation of backbone fibers from user connections
- Prevents external tampering due to key lock included in door
- Dust-tight protection against dust and low pressure water jets thanks to IP65 watertightness rating
- Suitable protection for installations exposed to shock due to IK08 impact resistance rating
- Screws for wall mounting are included
- Dimensions (W x H x D): 205mm x 258mm x 80mm
- White colour

Technical specifications : Ref. 231303

Number of fibers			24
Pre-cut openings			No
Independent compartments			No
Closure type			Door
Front door locking system			Key Lock, one-point lock
Type of connections			Connector and fusion splice
Installation type			Wall
Protection index (IP)			65
Protection index (IK)			08
Grounding			No
Material			ABS Plastic
Color			White
Height		in	10.157
Width		in	8.071
Depth		in	3.15