

Splitting Terminal Enclosure Up to 24 fibers

Designed to work as a pass-through and diverting element for optical fiber cables. It can be used both indoors and outdoors and allows the use of up to 12 SC Simplex or LC Duplex connectors, enabling quick connectorisation, as well as the use of pre-connectorised patch cords.
Can house up to 24 splices.

Ref.	231303
Logical ref.	OVB24A
EAN13	8424450259320

Packaging info	
Box	1 pcs.

Physical data	
Net weight	1,034.00 g
Gross volume	6.83 dm³
Gross weight	1,132.00 g
Width	200.00 mm
Height	250.00 mm
Depth	72.00 mm

Highlights

- Robust material due to ABS plastic construction
- Multi-fiber cable input/output of the main wiring system made by cones designed to house different fiber diameters
- Equipped with 2 stuffing gland at the bottom for optical fiber output
- Equipped with 1 removable tray, for easier installation and handling of the fibers
- Includes several areas for fiber confinement, allowing for easy separation of backbone fibers from user connections
- Prevents external tampering due to key lock included in door
- Dust-tight protection against dust and low pressure water jets thanks to IP65 watertightness rating
- Suitable protection for installations exposed to shock due to IK08 impact resistance rating

- Screws for wall mounting are included
- Dimensions (W x H x D): 205mm x 258mm x 80mm
- White colour

Technical specifications : Ref. 231303

Number of fibers		24
Pre-cut openings		No
Independent compartments		No
Closure type		Door
Front door locking system		Key Lock, one-point lock
Type of connections		Connector and fusion splice
Installation type		Wall
Protection index (IP)		65
Protection index (IK)		08
Grounding		No
Material		ABS Plastic
Color		White
Height	in	10.157
Width	in	8.071
Depth	in	3.15