



Ultra-compact Splitting Terminal Enclosure Up to 12 fibers

Designed to work as a pass-through and diverting element for optical fiber cables. Commonly used in FTTH projects, inside the buildings (usually in the secondary enclosure). Its ultra-compact and discreet design makes it easy to install without disturbing the aesthetics of the site. Can house up to 12 fibres.

Ref.	231304
Logical ref.	OVB12UK
EAN13	8424450266878

Packaging info

Box	1 pcs.
------------	--------

Physical data

Net weight	383.00 g
Gross weight	383.00 g
Width	136.00 mm
Height	136.00 mm
Depth	40.00 mm

Highlights

- Ultra-compact and discreet format
- Possibility to increase capacity up to 24 fibres with the extension frame (Ref. 231305)
- Built in high-resistance ABS
- Multi-fiber cable input/output of the main wiring through the side openings

- Security: screw fastening, to avoid external manipulation
- Grey colour (RAL 7035)
- Equipped with 1 trays, for up to 12 heat-shrink splices, vertically stacked, over the 6 positions it has
- Includes stows for different splices
- Screws for wall mounting are included
- Ingress protection code IP30 and impact protection code IK10
- Dimensions (W x H x D): 136mm x 136mm x 45mm

Technical specifications : Ref. 231304

Number of fibers			12
Pre-cut openings			No
Independent compartments			No
Closure type			Cover
Front door locking system			Screw
Type of connections			Fusion splice
Installation type			Wall
Protection index (IP)			30
Protection index (IK)			10
Grounding			No
Material			ABS Plastic
Colour			Grey
Height	mm		136
Width	mm		136
Depth	mm		45