



Ultra-compact Splitting Terminal Enclosure Up to 12 fibers

Designed to work as a pass-through and diverting element for optical fiber cables. Commonly used in FTTH projects, inside the buildings (usually in the secondary enclosure). Its ultra-compact and discreet design makes it easy to install without disturbing the aesthetics of the site. Can house up to 12 fibers.

Ref.	231304
Logical ref.	OVB12UK
EAN13	8424450266878

Packaging info

Box	1 pcs.
------------	--------

Physical data

Net weight	383.00 g
Gross volume	1.40 dm³
Gross weight	383.00 g
Width	136.00 mm
Height	136.00 mm
Depth	40.00 mm

Highlights

- Robust material due to ABS plastic construction
- Multi-fiber cable input/output of the main wiring through the side openings
- Equipped with 1 trays, for up to 12 heat-shrink splices, vertically stacked, over the 6 positions it

has

- Possibility to increase capacity up to 24 fibers with the extension frame (Ref. 231305)
- Includes stows for different splices
- Ultra-compact and discreet format
- External manipulations are made more difficult by the screw lock included in the door
- Protection against sprayed rain due to IP30 degree of watertightness
- Extremely high impact protection due to IK10 impact resistance rating
- Screws for wall mounting are included
- Dimensions (W x H x D): 136mm x 136mm x 45mm
- Grey colour (RAL 7035)

Technical specifications : Ref. 231304

Number of fibers		12
Pre-cut openings		No
Independent compartments		No
Closure type		Cover
Front door locking system		Screw
Type of connections		Fusion splice
Installation type		Wall
Protection index (IP)		30
Protection index (IK)		10
Grounding		No
Material		ABS Plastic
Color		Grey
Height	in	5.354
Width	in	5.354
Depth	in	1.772