



## Splitting Terminal Enclosure Up to 8 fibers

Designed to work as a final element for optical fiber cables. Commonly used in FTTH projects, inside the buildings (usually in the secondary enclosure).

Can house up to 8 splices and 8 SC Simplex or LC Duplex adapters.

It includes 8 rubber caps for the openings, preventing the entry of dust or other elements when the connectors are not installed, keeping the inside of the enclosure clean.

<b>Ref.</b>	231310
<b>Logical ref.</b>	OSB8
<b>EAN13</b>	8424450174852

### Packaging info

<b>Box</b>	1 pcs.
------------	--------

### Physical data

<b>Net weight</b>	696.00 g
<b>Gross volume</b>	1.90 dm <sup>3</sup>
<b>Gross weight</b>	696.00 g
<b>Width</b>	210.00 mm
<b>Height</b>	170.00 mm
<b>Depth</b>	38.00 mm
<b>Main product weight</b>	696.00 g

### Highlights

- Robust material due to steel construction

- Multi-fiber input through a PG9 stuffing gland
- Possibility of installation without connectors: By perforating the caps for the passage of the fiber, keeping the gap sealed
- Equipped with a support that can house up to 8 splices
- Including 8 heat-shrink protective sleeves for the fusions and 8 fixing flanges for the correct arrangement inside the register
- External tampering is made more difficult by the screw lock on the door (can be operated manually)
- Screws for wall mounting are included
- Dimensions (W x H x D): 210mm x 170mm x 38mm
- Grey colour (RAL 7035)

## Technical specifications : Ref. 231310

Number of fibers			8
Number of tube inlets			1.0000
Pre-cut openings			No
Independent compartments			No
Closure type			Door
Front door locking system			Screw
Type of connections			Connector and fusion splice
Installation type			Wall
Grounding			No
Material			Steel
Color			Grey
Height	in		6.693
Width	in		8.268
Depth	in		1.496