



## Optical fiber Patch/Splitting Box 1 to 4 outputs. 2 SC/APC adapters included

Device enabled as a connection point to an optical fiber network. In communications infrastructures, it works as a cut-off and test point for the optical fiber network. Thanks to the design, it also allows installation in other types of premises (car repair shops, classrooms, etc.) and is used as a connection point for optical fiber (work table, wiring cabinets, DIN rails, etc.) or else as an optical distribution frame, housing a 2 or 4-way optical splitter.

<b>Ref.</b>	231502
<b>Logical ref.</b>	OB4
<b>EAN13</b>	8424450183724

### Packaging info

<b>Box</b>	1 pcs.
------------	--------

### Physical data

<b>Net weight</b>	122.00 g
<b>Gross weight</b>	122.00 g
<b>Width</b>	118.00 mm
<b>Height</b>	96.00 mm
<b>Depth</b>	33.00 mm
<b>Main product weight</b>	84.00 g

### Highlights

- Made of robust ABS plastic. White color (RAL 9003)
- With a capacity of up to 4 SC/APC output connectors
- Equipped with 2 Simplex Single-Mode "SC/APC" female-to-"SC/APC" female adapters (with self-locking cover)
- Multi-anchoring system: Standard DIN rail, wall or outlet
- Single direction of rotation of the fibers inside (which facilitates installation)
- Identifying label
- 6 inputs, pre-cut on its sides, for FO access
- Back input for FO and SC connector
- Pre-cut input at the bottom, for access to a distribution frame (SC/APC)
- Equipped with: 2 heat-shrink sleeves, 2 cable ties, installation screws
- 100% european quality: manufactured by Televes in Spain

## Technical specifications : Ref. 231502

Number of inputs		8
Closure type		Cover
Front door locking system		Screw
Type of connections		Connector and fusion splice
Installation type		Wall / Ceiling
Material		ABS Plastic
Thickness	mm	2
Colour		White
Protection index (IP)		30
Protection index (IK)		7
Height	mm	97
Width	mm	119
Depth	mm	33
Blocking jelly		No
Operating temperature	°C	-20 ... 70