



F.O. Patch Box pre-terminated with dispenser box 4 SC/APC outputs

Device enabled as a connection point to an optical fiber network. In communications infrastructures, it works as a cut-off and test point for the optical fiber network.

The patch box includes Cca fiber, so it is recommended for installation in singular buildings (airports, hospitals, shopping centres, schools, universities), which require high levels of safety due to their large concurrence of people. Euroclass Cca guarantees an adequate level of safety in terms of reaction to fire and emission of toxic fumes, reducing the risks derived from a fire.

It incorporates optical fiber with one end pre-connectorised on the Patch Box, with 4 SC/APC connectors. This provides the installer with greater convenience and agility in assembly, allowing the fiber to pass through the different conduits to the desired point. The installer only has to do the fusion or connection 4 FO connectors at the connection point.

Moreover, the fiber is delivered in a dispenser box with a reel inside, which significantly facilitates the deployment of the cable, reducing installation time and the risk of damage to the fiber.

The design also allows installation in other types of premises (car repair shops, classrooms, work tables, wiring cabinets, etc.) and use as a connection point.

Ref.	231532
Logical ref.	OB4-4-40
EAN13	8424450186978

Other features

Length	40.00 m
---------------	---------

Packaging info

Box	1 pcs.
------------	--------

Physical data

Net weight	576.00 g
Gross volume	4.40 dm ³
Gross weight	576.00 g
Width	119.00 mm
Height	94.00 mm
Depth	34.00 mm




Highlights

- Made of robust ABS plastic. White color (RAL 9003)
- With a capacity of up to 4 SC/APC output connectors
- 100% laboratory verified by interferometer.
- Equipped with ITU-T G657A2 single-mode fibers and Cca Euroclass
- 100% laboratory verified by interferometer.
- Equipped with 4 Simplex Single-Mode "SC/APC" female-to-"SC/APC" female adapters (with self-locking cover)
- Multi-anchoring system: Standard DIN rail, wall or outlet
- Single direction of rotation of the fibers inside (which facilitates installation)
- Identifying label
- 6 inputs, pre-cut on its sides, for FO access
- Back input for FO and SC connector
- Pre-cut input at the bottom, for access to a distribution frame (SC/APC)
- Equipped with: 4 heat-shrink sleeves, 2 cable ties, installation screws

- 100% european quality: manufactured by Televes in Spain

Mounting details

1. Select the most suitable entry for the fibre optic hose, maintaining a smoothly curved fibre path
2. Cut in the cover the appropriate tab to used entry
3. Fit the fibre to the Patch Box, fix it with cable ties at the anchor points and connect it to the adapters
4. Fix the Patch Box either to the wall, using the screws supplied, or to DIN by removing the pre-cut tabs on the cover



Technical specifications : Ref. 231532

Number of fibers		4
Number of inputs		8
Closure type		Cover
Front door locking system		Screw
Type of connections		Connector and fusion splice
Installation type		Wall / Ceiling
Material		ABS Plastic
Thickness	in	0.079
Color		White
Protection index (IP)		30
Protection index (IK)		07
Height	in	3.819
Width	in	4.685
Depth	in	1.299
Fiber core type		Single-mode (ITU-T-G.657.A2)
Euroclass		Cca
Euroclass: Smoke Production		s1a
Euroclass: Flaming droplets		d1
Euroclass: Acidity		a1
Fiber core diameter	µm	9
Fiber cladding diameter	µm	125
Coating buffer diameter	µm	250
Cable structure		Tight buffer
Outer sheath Diameter	in	0.118
Outer sheath Material		LSFH
Blocking jelly		No
Optical fiber attenuation: 1310nm	dB/km	< 0.4
Optical fiber attenuation: 1550nm	dB/km	< 0.3
Optical fiber attenuation: 1490nm	dB/km	< 0.3
Connector losses	dB	< 0.5
Return losses	dB	> 60
Short tension	N	220
Long tension	N	220
Structure reinforcement element		Aramid fibers
Minimum bending radius	in	0.591
Operating temperature	°F	-4 ... 158