



Fiber kabel FK4 Single-Mode 4 fiber, Cca Euroclass och LSFH, inomhus

4-Fiber kabel med LSFH-hölje för installation inomhus. Varje fiber kan identifieras genom en egen specifik färg. Detta skapar bättre ordning och gör identifiering enklare. Levereras på plastbopin, i 500m.

Ref.	231942
	OSK4I-500
EAN13	8424450273029

Andra funktioner

Färg	Orange
Längd	500,00 m

Förpackning

Rulle	500 m
Låda	1500 m

Fysisk data

Nettovikt	11,00 g
Bruttovolym	0,05 dm ³
Bruttovikt	11,00 g
Bredd	3,00 mm
Höjd	1.000,00 mm
Djup	3,00 mm
Huvudproduktens vikt	11,00 g

Utmärkande egenskaper

- Låg dämpning
- Med aramid fiber för att stärka strukturen

- Cca Euroclass
- 9/125, ITU-T G.657.A2 fiber typ
- Coating diameter för lös tub (250 µm)
- LSFH-hölje i orange färg

Tekniska specifikationer : Ref. 231942

Euroclass		Cca
Euroclass: Smoke Production		s1a
Euroclass: Flaming droplets		d1
Euroclass: Acidity		a1
Fiber core type		Single-mode (ITU-T-G.657.A2)
Fiber core diameter	µm	9
Fiber cladding diameter	µm	125
Coating buffer diameter	µm	250
Cable structure		Loose tube
Outer sheath Diameter	mm	3
Outer sheath Material		LSFH
Blocking jelly		Yes
Attenuation 1310nm	dB/km	< 0,4
Attenuation 1550nm	dB/km	< 0,3
Long tension	N	220
Structure reinforcement element		Aramid fibers
Minimum bending radius	mm	15
Operating temperature	°C	0 ... 60