



## Pigtails SC/APC, Single-mode (SM), LSFH indoor

Single-mode (SM) pigtail, used for interconnecting optical equipment, have its end pre-terminated with SC/APC connectors.

The 900µm cover is of LSFH type and is recommended for indoor use. Additionally, its pre-terminated end has a short boot, facilitating installation in wall sockets, avoiding increases in attenuation due to undesirable bends, allowing the sliding of the patch cord through conduits, reducing the space required for connection, and being less demanding regarding bend radius.

<b>Ref.</b>	232603
<b>Logical ref.</b>	OSCAPC1
<b>EAN13</b>	8424450259306

### Other features

<b>Colour</b>	White
<b>Supply method</b>	Multiple packing (25 units)
<b>Length</b>	1.00 m

### Packaging info

<b>Box</b>	25 pcs.
------------	---------

### Physical data

<b>Net weight</b>	4.00 g
<b>Gross volume</b>	0.02 dm <sup>3</sup>
<b>Gross weight</b>	8.00 g
<b>Width</b>	9.00 mm
<b>Height</b>	1,120.00 mm
<b>Depth</b>	8.00 mm
<b>Main product weight</b>	4.00 g

## Highlights

---

- ITU-T G.657.A2 fiber type
- LSFH sheath, white colour
- SC/APC connectors
- 1m long

## Technical specifications : Ref. 232603

Fiber core type		Single-mode (ITU-T-G.657.A2)
Fiber core diameter	μm	9
Fiber cladding diameter	μm	125
Cable structure		Tight buffer
Outer sheath Diameter	μm	900
Outer sheath Material		LSFH
Attenuation 1310nm Max	dB/km	0.4
Attenuation 1550nm Max	dB/km	0.3
Cable length	m	1
Insertion losses Max	dB	0.5
Return losses Min	dB	60
Optical connector type		SC
Polishing type (Optical connector)		APC
Operating temperature	°F	-4 ... 158