



## Optical fiber patch cord SC/APC, Single-mode (SM), LSFH and Dca Euroclass indoor

Single-mode (SM) optical-fiber patch cord Pre-terminated with SC/APC connectors for the connection of the elements of an optical network. The sheath being LSFH, it is recommended for indoor use.

It has an end with a short boot that facilitates installation in wall sockets, avoiding attenuation increases due to undesired bending. In addition, the short boot facilitates the sliding of the patch cord through the conduits, reduces the space required for connection and the bending radius is less demanding.

Supplied in individual packing.

<b>Ref.</b>	232612
<b>Logical ref.</b>	OSK15SCAPC
<b>EAN13</b>	8424450222911

### Other features

<b>Colour</b>	Orange
<b>Length</b>	15.00 m

### Packaging info

<b>Bag</b>	1 pcs.
------------	--------

### Physical data

<b>Net weight</b>	127.00 g
<b>Gross weight</b>	127.00 g

## Highlights

---

- Low attenuation levels and high reliability
- Short boot at one end: allows a smaller bending radius and better use of space in the connection area
- Dca-s2,d2,a1 Euroclass
- ITU-T G.657.A2 fiber type
- LSFH sheath, orange colour
- SC/APC connectors
- Available in different lengths

## Technical specifications : Ref. 232612

Euroclass		Dca
Euroclass: Smoke Production		s2
Euroclass: Flaming droplets		d2
Euroclass: Acidity		a1
Fiber core type		Single-mode (ITU-T-G.657A2)
Optical fiber type category		OS1
Fiber core diameter	µm	9
Fiber cladding diameter	µm	125
Coating buffer diameter	µm	250
Cable structure		Tight buffer
Plastic buffer diameter	mm	0.85
Outer sheath Diameter	mm	3
Outer sheath Material		LSFH
Blocking jelly		No
Attenuation 1310nm	dB/km	< 0,8
Attenuation 1490nm	dB/km	< 0,8
Attenuation 1550nm	dB/km	< 0,8
Insertion losses in connector 1	dB	< 0,5
Insertion losses in connector 2	dB	< 0,5
Return losses in connector 1	dB	> 60
Return losses in connector 2	dB	> 60
Optical connector type 1		SC
Polishing type (Optical connector 1)		APC
Optical connector type 2		SC
Polishing type (Optical connector 2)		APC
Short tension	N	450
Long tension	N	200
Structure reinforcement element		Aramid fibers
Short crush (@100mm)	N	500
Long crush (@100mm)	N	100
Minimum bending radius	mm	15
Operating temperature	°C	-20 ... 70