



Optical fiber patch cord SC/APC, Single-mode (SM), LSFH and Dca Euroclass indoor

Single-mode (SM) optical-fiber patch cord Pre-terminated with SC/APC connectors for the connection of the elements of an optical network. The sheath being LSFH, it is recommended for indoor use.

It has an end with a short boot that facilitates installation in wall sockets, avoiding attenuation increases due to undesired bending. In addition, the short boot facilitates the sliding of the patch cord through the conduits, reduces the space required for connection and the bending radius is less demanding.

Supplied in individual packing.

Ref.	232613
Logical ref.	OSK20SCAPC
EAN13	8424450265604

Other features

Colour	Orange
Length	20.00 m

Packaging info

Bag	1 pcs.
------------	--------

Physical data

Net weight	159.00 g
Gross weight	167.00 g
Width	3.00 mm
Height	20,000.00 mm
Depth	3.00 mm
Main product weight	159.00 g

Highlights

- Low attenuation levels and high reliability
- Short boot at one end: allows a smaller bending radius and better use of space in the connection area
- Dca-s2,d2,a1 Euroclass
- ITU-T G.657.A2 fiber type
- LSFH sheath, orange colour
- SC/APC connectors
- Available in different lengths

Technical specifications : Ref. 232613

Euroclass			Dca
Euroclass: Smoke Production			s2
Euroclass: Flaming droplets			d2
Euroclass: Acidity			a1
Fiber core type			Single-mode (ITU-T-G.657.A2)
Optical fiber type category			OS1
Fiber core diameter	µm		9
Fiber cladding diameter	µm		125
Coating buffer diameter	µm		250
Cable structure			Tight buffer
Plastic buffer diameter	mm		0.85
Outer sheath Diameter	mm		3
Outer sheath Material			LSFH
Blocking jelly			No
Attenuation 1310nm	dB/km		< 0.8
Attenuation 1490nm	dB/km		< 0.8
Attenuation 1550nm	dB/km		< 0.8
Insertion losses in connector 2	dB		< 0.5
Return losses in connector 2	dB		> 60
Optical connector type 1			SC
Polishing type (Optical connector 1)			APC
Optical connector type 2			SC
Polishing type (Optical connector 2)			APC
Cable length	m		20
Short tension	N		450
Long tension	N		200
Structure reinforcement element			Aramid fibers
Short crush (@100mm)	N		500
Long crush (@100mm)	N		100
Minimum bending radius	mm		15
Operating temperature	°C		-20 ... 70