

Single-mode (SM) optisk fiber förkontakterad För inomhusbruk LSFH SC/APC – SC/UPC, Single-mode (SM)

Single-mode (SM) optisk fiber förkontakterad med SC/APC-kontakt i ena änden och SC/UPC på andra sidan för att anpassa olika anslutningar vid sammankopplingen av optisk utrustning.

Ref.	232622
	OSK20SCPC
EAN13	8424450188699

Andra funktioner	
Färg	Orange
Längd	0,20 m

Förpackning	
Påse	1 st.
Låda	5 st.

Fysisk data	
Nettovikt	11,00 g
Bruttovolym	0,54 dm³
Bruttovikt	11,00 g
Bredd	3,00 mm
Höjd	200,00 mm
Djup	3,00 mm
Huvudproduktens vikt	11,00 g

Utmärkande egenskaper

- Fiber typ ITU-T G.657.A2
- LSFH, orange färg
- SC-kontakter med APC i ena änden och UPC på den andra
- Längd 0,2m

Tekniska specifikationer : Ref. 232622

Fiber core type		Single-mode (ITU-T-G.657.A2)
Optical fiber type category		OS1
Fiber core diameter	µm	9
Fiber cladding diameter	µm	125
Coating buffer diameter	µm	250
Cable structure		Tight buffer
Outer sheath Diameter	mm	3
Outer sheath Material		LSFH
Blocking jelly		No
Attenuation 1310nm	dB/km	< 0,4
Attenuation 1550nm	dB/km	< 0,3
Insertion losses in connector 2	dB	< 0,5
Return losses in connector 2	dB	> 50
Optical connector type 1		SC
Polishing type (Optical connector 1)		APC
Optical connector type 2		SC
Polishing type (Optical connector 2)		UPC
Cable length	m	0,2
Minimum bending radius	mm	15
Operating temperature	°C	-20 ... 70