



## FC/UPC 4W optical splitter 1260...1650 nm 7 dB

4-way splitter with FC/UPC connectors for optical signals in the 1260 nm-to-1650 nm range. Recommended for wideband LNB based applications, or any type of GPON network. The compact frame is perfect for individual installations.

<b>Ref.</b>	235901
<b>Logical ref.</b>	OVT4N
<b>EAN13</b>	8424450152454

### Packaging info

<b>Box</b>	1 pcs.
<b>Bucket</b>	50 pcs.

### Physical data

<b>Net weight</b>	239.00 g
<b>Gross volume</b>	1.02 dm <sup>3</sup>
<b>Gross weight</b>	239.00 g
<b>Width</b>	115.00 mm
<b>Height</b>	151.00 mm
<b>Depth</b>	20.00 mm
<b>Main product weight</b>	239.00 g

### Highlights

- High reliability
- High uniformity among outputs

- Low insertion losses
- Made in single-mode fiber (SM)
- FC/UPC connectors

## Technical specifications : Ref. 235901

Number of outputs		4
Optical connectors Input		FC/UPC
Optical connectors Output		FC/UPC
Fiber type		Single-Mode
Coupling ratio (per output)		Symmetrical
Wavelength	nm	1310 ... 1550
Insertion losses	dB	< 7,6
Return losses	dB	> 50
Uniformity	dB	< 0,6
Polarization loss (PDL)	dB	< 0,2
Directivity	dB	> 50
Operating temperature	°F	-40 ... 185