



## FC/UPC 8W optical splitter 1260...1650 nm 10.1 dB

8-way splitter with FC/UPC connectors for optical signals in the 1260 nm-to-1650 nm range. Recommended for wideband LNB based applications, or any type of GPON network. The compact frame is perfect for individual installations.

Ref.	236001
Logical ref.	OVT8N
EAN13	8424450152461

### Packaging info

Box	1 pcs.
Bucket	50 pcs.

### Physical data

Net weight	293.00 g
Gross weight	293.00 g
Width	115.00 mm
Height	164.00 mm
Depth	20.00 mm
Main product weight	293.00 g

### Highlights

- High reliability
- High uniformity among outputs
- Low insertion losses

- Made in single-mode fiber (SM)
- FC/UPC connectors

## Technical specifications : Ref. 236001

Number of outputs		8
Optical connectors Input		FC/UPC
Optical connectors Output		FC/UPC
Fiber type		Single-Mode
Coupling ratio (per output)		Symmetrical
Wavelength	nm	1310 ... 1550
Insertion losses	dB	< 10.7
Return losses	dB	> 50
Uniformity	dB	< 0.8
Polarization loss (PDL)	dB	< 0.2
Directivity	dB	> 50
Operating temperature	°C	-40 ... 75