



## Straight bracket with U-shaped profile, 300mm Zinc + RCP

Straight bracket with U-shaped profile for mast wall mounting (screw mounting), and 300mm separation. Installed in pairs to secure the mast in two spots.

Steel mast with an outstanding resistance to corrosion, thanks to the double treatment consisting in galvanizing and reactive coating process (RCP).

|              |               |
|--------------|---------------|
| <b>Ref.</b>  | 240410        |
| <b>EAN13</b> | 8424450190272 |

### Other features

|               |      |
|---------------|------|
| <b>Colour</b> | Grey |
|---------------|------|

### Packaging info

|            |        |
|------------|--------|
| <b>Box</b> | 6 pcs. |
|------------|--------|

### Physical data

|                              |            |
|------------------------------|------------|
| <b>Photo with dimensions</b> | 2.00       |
| <b>Net weight</b>            | 1,513.00 g |
| <b>Gross volume</b>          | 17.57 dm³  |
| <b>Gross weight</b>          | 1,713.00 g |
| <b>Width</b>                 | 125.00 mm  |
| <b>Height</b>                | 300.00 mm  |
| <b>Depth</b>                 | 125.00 mm  |
| <b>Main product weight</b>   | 1,513.00 g |

### Highlights

- Zinc coating + RCP: Outstanding resistance to corrosion
- Compatible with 35 mm-to-50 mm mast diameter range (Ø 35...50 mm)
- Includes U-bolt and nuts

Technical specifications : Ref. 240410

|                  |    |                 |
|------------------|----|-----------------|
| Support model    |    | Wall mount      |
| Support material |    | Steel           |
| Mast diameter    | in | 1.378 ... 1.969 |
| Distance         | in | 11.811          |