



Through outlet 2 connectors: FM-TV, Attenuation: 6dB

Through outlet with two IEC connectors. The left connector is a male IEC for terrestrial TV, the right connector is a female IEC for radio (FM). Equipped with signal pass-through, which allows serial connection of multiple outlets. Installation with ref. 523211 terminal outlets is recommended.

DOCSIS 3.1 compatible.

Ref.	523310
Logical ref.	BKD1218-6ST
EAN13	8424450208540

Packaging info

Box	1 pcs.
Carton	10 pcs.
Carton	100 pcs.
Pallet	3600 pcs.

Physical data

Net weight	90.00 g
Gross volume	0.17 dm ³
Gross weight	90.00 g

Highlights

- Robot-controlled automated manufacturing
- High shielding
- Made of Zamak, high strength
- Compatible with coaxial cable with sheath diameters in the 4.3-to-6,9 mm range (Ø 4.3...6,9 mm)

- With clamp

Technical specifications : Ref. 523310

Fastening method			Without screws	
Number of connectors			2	
R Connector			"IEC" female	
TV Connector			"IEC" male	
Pass-through output			Yes	
Bands				
Frequency range	MHz	FM		TV
		87.5 ... 108		5 ... 1220
Through losses	dB	2.5		2.5
Attenuation: R Connector	dB	6		--
Attenuation: TV Connector	dB	--		6
DC pass			OutIn	
Max. current	mA		500	