



## Through outlet 2 connectors: FM-TV, Attenuation: 8dB

Through outlet with two IEC connectors. The left connector is a male IEC for terrestrial TV, the right connector is a female IEC for radio (FM). Equipped with signal pass-through, which allows serial connection of multiple outlets. Installation with ref. 523211 terminal outlets is recommended.

DOCSIS 3.1 compatible.

|                     |               |
|---------------------|---------------|
| <b>Ref.</b>         | 523311        |
| <b>Logical ref.</b> | BKD1218-8ST   |
| <b>EAN13</b>        | 8424450208557 |

### Packaging info

|               |           |
|---------------|-----------|
| <b>Box</b>    | 1 pcs.    |
| <b>Carton</b> | 10 pcs.   |
| <b>Carton</b> | 100 pcs.  |
| <b>Pallet</b> | 3600 pcs. |

### Physical data

|                     |          |
|---------------------|----------|
| <b>Net weight</b>   | 90.00 g  |
| <b>Gross volume</b> | 0.17 dm³ |
| <b>Gross weight</b> | 90.00 g  |

### Highlights

- Robot-controlled automated manufacturing
- High shielding
- Made of Zamak, high strength
- Compatible with coaxial cable with sheath diameters in the 4.3-to-6,9 mm range (Ø 4.3...6,9 mm)

- With clamp

Technical specifications : Ref. 523311

|                           |     |              |                |            |
|---------------------------|-----|--------------|----------------|------------|
| Fastening method          |     |              | Without screws |            |
| Number of connectors      |     |              | 2              |            |
| R Connector               |     |              | "IEC" female   |            |
| TV Connector              |     |              | "IEC" male     |            |
| Pass-through output       |     |              | Yes            |            |
| Bands                     |     |              |                |            |
| Frequency range           | MHz | FM           |                | TV         |
|                           |     | 87.5 ... 108 |                | 5 ... 1220 |
| Through losses            | dB  | 2.5          |                | 2.5        |
| Attenuation: R Connector  | dB  | 8            |                | --         |
| Attenuation: TV Connector | dB  | --           |                | 8          |
| DC pass                   |     |              | OutIn          |            |
| Max. current              | mA  |              | 500            |            |