



Through outlet 3 connectors: FM-TV-SAT

Three-connector through outlet The IEC male connector for terrestrial TV is located on the lower left side, while the IEC female connector for FM (radio) is located on the lower right side; an F connector for satellite TV (SAT) is located at the top centre.

Equipped with signal pass-through, which allows serial connection of multiple outlets. The lower part of the chassis is open.

Ref.	524201
Logical ref.	SD33ST-DC
EAN13	8424450148044

Packaging info

Box	1 pcs.
Carton	10 pcs.
Carton	100 pcs.
Pallet	25000 pcs.

Physical data

Net weight	94.00 g
Gross volume	0.25 dm ³
Gross weight	94.00 g
Width	70.00 mm
Height	67.00 mm
Depth	36.00 mm
Main product weight	93.00 g

Highlights

- Robot-controlled automated manufacturing

- High shielding
- Outstanding isolation between outputs
- Made of Zamak, high strength
- DC pass from the SAT connector to the input, and bidirectional circulation between the input and the output with DC bypass
- Compatible with coaxial cable with sheath diameters in the 5-to-6,9 mm range (Ø 5...6,9 mm)

Discover

Televes outlets: Screw-free mounting

A class A outlet offering numerous advantages:

- The inner conductor is connected simply by pushing, without the need for screws; still the gripping force is equivalent
- Supports inner conductor diameters from 0.65 mm to 1.2 mm, and external cable diameters from 5 mm to 6.9 mm
- F-connector type conic guide for easy inner conductor introduction
- Wide margin in inner conductor length (from 5 mm to 15 mm), which makes short circuits between core and mesh difficult
- Tilt-up, self-supporting, full-opening clamp
- The clamp is equipped with 3 jagged rows in 9 mm for a perfect braid fixing
- Printed circuit board perforation to make the faceplate fixing screw compatible
- Rounded edges to prevent cuts
- Class A shielding

Furthermore, this product range includes several engravings on the chassis:

- CE marking
- Numerical and logical references
- Input and output indications

- Cable stripping dimensions

Technical specifications : Ref. 524201

Fastening method			Without screws	
Number of connectors			3	
R Connector			"IEC" female	
TV Connector			"IEC" male	
SAT Connector			"F" female	
Pass-through output			Yes	
Bands		FM	TV	SAT
Frequency range	MHz	87.5 ... 108	115 ... 862	950 ... 2150
Rejection between outputs	dB	> 15	> 11	> 10
Through losses	dB	2.5	2.5	3.5
Attenuation: R Connector	dB	15	--	--
Attenuation: TV Connector	dB	--	11	--
Attenuation: SAT Connector	dB	--	--	10
DC pass			SAT□In / Out□In	
Max. current	mA		500	