



## 19"-Rack Cabinet 15+2RU 600x450 mm

The 15+2RU rack Cabinet is used for the housing of active or passive equipment, visible from the outside and protected by a safe steel lockable structure. Compatible with optical fiber, data cables or coaxial cable installations, it allows the grouping of different technologies in a single cabinet.

Total capacity is 17RU, namely 15RU and an additional 2RU, taking advantage of the top and bottom ends. The rack is equipped with depth-adjustable side profiles, which allow the installation of different types of panels or equipment.

It has a reversible and removable front door with a flexible fit, which facilitates working in the rack. The tempered glass door allows viewing the status of the devices without opening the rack. It also has push-button removable side doors for access to the rack interior through the sides, an advantage when configuring rear connections.

It is designed for wall or floor installation. In addition, it includes a bracket for wall mounting. The independent bracket facilitates installation, since it allows marking the drilling points to screw it to the wall and, after that, to place the rack on it.

---

<b>Ref.</b>	533115
<b>Logical ref.</b>	MSR1915
<b>EAN13</b>	8424450271728

---

## Other features

<b>Supply method</b>	Assembled
<b>Rack depth</b>	450mm
<b>Height (RU)</b>	15+2RU
<b>Perforated doors</b>	

## Packaging info

<b>Box</b>	1 pcs.
------------	--------

## Physical data

<b>Net weight</b>	30,000.00 g
<b>Gross volume</b>	208.17 dm <sup>3</sup>
<b>Gross weight</b>	33,000.00 g
<b>Width</b>	600.00 mm
<b>Height</b>	771.00 mm
<b>Depth</b>	450.00 mm
<b>Main product weight</b>	30,000.00 g

## Highlights

- High strength and durability: made of steel, with a coating based on polyester resins and lead-free pigments
- Safety: Tempered glass, lockable hinged front door
- Laser marking: numerical identification of each "RU"
- Horizontal cable guides: 1RU cable panels located at the top and bottom of the cabinet to lead cabling from one side to the other and facilitate connections
- Additional supports: includes 2 side profiles as standard to reinforce shelf installation, especially in high-load configurations
- Electrical safety: Each door and removable panel includes a grounding screw (terminal) to ensure proper grounding connection
- A 120x120 mm ventilation kit can be incorporated for the installation of active equipment, such as headends

## Discover

REF.	DIMENSIONS (mm)	RACK UNITS (RU)	INSTALLATION	COMPATIBLE WITH			
Compatibility of our racks with fans, wheels, plinths and cable management panels				FAN	WHEELS	PLINTH	CABLE MANAGEMENT

533105/06	600x450	6+2	to ensuring the performance, accessibility and		
533107/08	600x450	8+2	organisation of the entire infrastructure. Elements such as fans, wheels, plinths and cable management		
533112/13	600x450	13+2	panels help optimise cooling, mobility and cable routing.	Wall / Floor	533174 Not applicable Not applicable
533114/15	600x450	15+2			
533111/16	600x600	15+2	Our racks are equipped with natural ventilation, but for applications requiring greater thermal		
533119/18	600x600	18	control, it is possible to incorporate active ventilation systems with fans, significantly improving		533158 533159 533160
533121/22	600x600	22	thermal management.		
533126/27	600x600	27		533175	
533131/32	600x600	32	Another option for standard racks include feet, but it is also possible to add wheels. In this way, a rack can be		
533136/37	600x600	37	installed either on feet only, on wheels, or with a combination of both. This configuration		
533138/39	600x800	37	provides great flexibility, allowing the rack to be moved easily during installation or maintenance,		
533141/42	600x800	42	to correct floor unevenness and to distribute the load across more support points.	Floor	533171
533128	800x800	27	Another option available for certain racks is installation on plinths. Plinths elevate the cabinet		533158 533159 533160
533143/44	800x800	42	from the floor, making maintenance easier and improving the stability of the assembly.	533176	533156
533149/45	800x800	42	Additional space also allows cable routing and concealment at the bottom section, guiding it		533158
533148/46	800x1000	42	neatly towards the rear, contributing to a cleaner and more organised installation.		533159 533160
533149/47	800x1000	42	Another option for cable management is the use of cable management panels. These enable		533167

efficient cable routing inside the rack, facilitating both installation and maintenance operations. Their use improves equipment accessibility and contributes to a more orderly and professional setup. They are available in horizontal and vertical configurations, adapting to the needs of each installation.

Below is a compatibility table for our racks with all these accessories:

## Technical specifications : Ref. 533115

Modular spacing (standard)	in	19
Height	in	30.354
Width	in	23.622
Depth	in	17.717
Number of rack units (RU)		15
Material		Steel
Rack rail thickness	in	0.059
Color		Black
Surface finishing		Electrostatic powder
Number of doors		1
Front door material		Tempered glass
Rear door		No
Max. load capacity	kg	60
Removable sides		Yes
Installation type		Wall / Ground
Type of profile rail		L-shaped
Grounding		Yes
Protection index (IP)		20
Protection index (IK)		07