



## Splice Box for Rack 19" For "SC" Simplex or "LC" Duplex optical adapters

Designed to house SC-to-SC Simplex or LC-to-LC Duplex adapters, it can be used as a junction point for optical fibers (FO patch panel). It can be used to easily connect segregated multifiber hoses or several fiber hoses, thus allowing easy access and identification of these.

It allows having a fixed optical fiber distribution network, to which different signals can be delivered just by a reconnection on the panel. Thanks to its wide design, it facilitates the easy assembly and maintenance of the fusion patches that it houses. In addition, the position of the splice box can be set back with respect to the rack profile, in order to protect the connectors against knocks or chafing, and to allow the door to close without any problem.

<b>Ref.</b>	533152
<b>Logical ref.</b>	UFB24SC-A
<b>EAN13</b>	8424450182598

### Other features

<b>Number of connectors</b>	24 SC Simplex or LC Duplex adapters
<b>Height (RU)</b>	1RU

### Physical data

<b>Net weight</b>	1,342.00 g
<b>Gross volume</b>	7.57 dm <sup>3</sup>
<b>Gross weight</b>	1,629.00 g

## Packaging info

---

**Box** 1 pcs.

---

**Carton** 5 pcs.

---

**Width** 480.00 mm

---

**Height** 42.00 mm

---

**Depth** 230.00 mm

---

**Main product weight** 1,342.00 g

---

## Highlights

---

- Resistant material due to steel construction of frame and rails
- Lightweight base due to aluminium construction
- Each connector is identified with a laser-marked number
- Black colour (RAL 9005)
- Includes 4 screws and 4 nuts for installation in a 19"-rack
- Equipped with a FO tray and cover to house the different fiber splices
- Includes clamps and flanges for the fixing and guiding of the different fibers

## Technical specifications : Ref. 533152

Modular spacing (standard)	in	19
Number of rack units (RU)		1
Optical connector type		LC Duplex / SC Simplex
Max. capacity of connectors		24
Depth	in	9.291
Depth adjustment	in	2.165
Color		Black