



Kit: Low-gain mast amplifier and PicoKom Power Supply Unit Ref. 536023 + Ref. 579401

The kit consists of:

Ref. 536023: Low-gain mast amplifier, 3 inputs: BIII/DAB-UHF-UHF

Masthead amplifier for the amplification of terrestrial television signals coming from several antennas.

Equipped with 3 inputs, with amplification on all bands. The amplifier is powered through the output coaxial cable at 12 Vdc. Red compliant.

Ref. 579401: PicoKom power supply unit, 12V - 220mA, 2 outputs

Domestic 12 V-power supply (200 mA) that powers equipment through the input coaxial cable while allowing the transmission of the TV signal. Included in the installation to power either mast amplifiers or a BOSS system. Furthermore, it is equipped with two outputs.

Ref.	536012
EAN13	8424450228630

Other features

Colour	Orange
---------------	--------

Physical data

Net weight	555.00 g
Gross volume	1.27 dm ³

Packaging info

Box	1 pcs.
-----	--------

Gross weight

555.00 g

Highlights

- Independent amplification for each individual band
- EasyF connection system
- LTE/5G filter to remove mobile phone interference
- ON/OFF switch to allow DC pass towards one of the UHF inputs for the powering of a BOSS system
- Easy mounting. Equipped with a plastic tie for mast mounting
- Orange enclosure for outdoor installation, made of durable ABS plastic with UV protection validated according to ISO 4892-3:2016
- Fully automated manufacturing, subject to the most stringent quality controls
- High-screening Zamak chassis

Discover

EasyF connection system: simplicity and savings

EasyF is an innovative connection concept where the inner conductor of the coaxial cable is directly inserted in the device, thus improving connection reliability. Thanks to the absence of F connectors, the chassis can be reduced and the connection of two cables secured with a single screw.

- Real time savings: speeding the installation is possible without the need for coaxial cable termination. Furthermore, there is no need for screwing the connectors on the device, which is sometimes difficult when there is little room
- Connection reliability: the clamp holding the cables prevents the coaxial cable to come off
- Cost savings: no additional connectors are required (neither F nor IEC)
- Space optimization: inputs and outputs are always on the same side of the device to prevent coaxial cables from bending, and to make working inside cabinets and register boxes easier

- Very easy three-step mounting: only screwing and unscrewing the covers is required to connect both cables:

1. Unscrew the device's cover to access the connection
2. Insert the previously stripped coaxial cables
3. Close the cover and screw to ensure connection

Learn more about EasyF system reliability

With EasyF, the connection between the coaxial cable and the device is carried out using an automated system for contact insertion of the inner conductor, without any soldering.

- Always as new: the device's operating life increases when the factor of solder wearing out with time is removed
- Failure rate reduction: usually produced as a result of cold soldering joints
- Electromagnetic behaviour optimization: for high frequencies

Why choose an amplifier with switchable LTE790/700 filter?

The anti-LTE filtering switch integrated in Televes amplifiers allows you to select the appropriate internal filter between channels 60 (790Mhz) or 48 (694MHz), adapting it to the DTT channeling frequencies of the region, so that it completely rejects the type of signal LTE that may interfere with the product.

This functionality offers versatility to maintain an installation free of interference in all LTE situations, covering the filtering requirements in any territory with a single amplifier, before, during and after the transition period. In addition, it simplifies the installation logistics, being only necessary to switch the filter to adapt the installation to the Digital Dividend operating in the region, and also allowing to adapt it to contingencies that may occur in the execution of the Dividend, in terms of delays or advances in its planning.

Technical specifications : Ref. 536012

Bands		HighVHF	UHF
Frequency range	MHz	174 ... 254	470 ... 790
Gain	dB	26	28
Gain adjustment range	dB	0 ... 18	0 ... 15
Output level DIN45004B	dBmV	49	54
Output level EN60728-3 IMD3 2tones -35dB	dBmV	55	61
Output level EN60728-3 IMD3 2tones -60dB	dBmV	45	51
Noise figure	dB	5	9
Number of inputs		3	
Inputs/Bands		HighVHF/DAB	UHF 1
Max current input	mA	0	0
Powering	Vdc	12	
Current consumption	mA	110	
Protection index (IP)		23	
Operating temperature	°F	23 ... 113	