



MiniKom F line broadband multiband amplifier 1 input: VHF/UHF

Line multiband amplifier (1 input/1 output) for MATV systems. Separate amplification guarantees the absence of intermodulation among inputs and independent attenuators per band (47 MHz- 454 MHz/ 470 MHz - 862 MHz).

Ref.	537310
EAN13	8424450178911

Other features

Plug type	US plug
------------------	---------

Packaging info

Box	1 pcs.
------------	--------

Physical data


Net weight	1,100.00 g
Gross volume	1.80 dm ³
Gross weight	1,100.00 g
Width	185.00 mm
Height	114.00 mm
Depth	64.00 mm
Main product weight	828.00 g

Highlights

- Separate amplification enhance the output level without causing any interference among bands
- PIN-diode technology gain attenuators on each input (0 dB-20 dB)

- Switched configurable gain (high/low), and high output level
- High-screening Zamak chassis
- “F” connectors
- Output signal LED indicator
- Test output (-30 dB)
- Switch for pre-amplifier or BOSS system powering
- Can be wall-mounted using screws

Application example



Technical specifications : Ref. 537310

Bands		VHF		UHF
Frequency range	MHz	47 ... 454		470 ... 862
High gain	dB	30		38
Low gain	dB	20		28
Noise figure	dB	6		6
Output level EN50083 IMD2 2tones -60dB	dBmV	43		--
Output level EN50083 IMD3 2tones -35dB	dBmV	61		63
Output level EN50083 IMD3 2tones -60dB	dBmV	51		53
Output level DIN45004B	dBmV	53		56
Input attenuator	dB		0 ... 20	
Max current input	mA	70		70
Max. power consumption	W		4.5	
Max. current	mA		65	
Input voltage	Vac		120 ... 230	
Mains frequency			50 Hz / 60 Hz	
Number of inputs			1	
Number of outputs			1	
Connectors			"F" type	
Operating temperature	°F		32 ... 113	
Protection index (IP)			20	