



## Power supply unit 12V - 3A

Device that converts alternating current into direct current to feed a wide range of equipment. Several plugs are included for its use in any electrical installation.

<b>Ref.</b>	593203
<b>Logical ref.</b>	H30-NT
<b>EAN13</b>	8424450173671

### Packaging info

<b>Box</b>	1 pcs.
------------	--------

### Physical data

<b>Net weight</b>	213.00 g
<b>Gross volume</b>	0.08 dm <sup>3</sup>
<b>Gross weight</b>	213.00 g
<b>Width</b>	78.00 mm
<b>Height</b>	96.00 mm
<b>Depth</b>	43.00 mm
<b>Main product weight</b>	164.00 g

### Highlights

- Multiplug (EU, UK, US and AUS)
- 3A maximum current
- Plug-in power supply
- 100 VAC-240 VAC supply voltage

- 12 V output voltage
- It is recommended not to exceed 65% of the maximum current of the PSU under continuous operating
- Wide range of operating temperatures
- Limited size

## Technical specifications : Ref. 593203

Plug type		AUS / EU / UK / US
Input voltage	Vac	100 ... 240
Mains frequency		50 Hz / 60 Hz
Output voltage	Vdc	12
Max. output current	A	3
Operating temperature	°F	23 ... 113
Protection index (IP)		20