



NevoSwitch equipped with 5 inputs and 8 outputs, with passive terrestrial

When quality matters

Multiswitch equipped with 5 inputs (one passive terrestrial, and the four polarities of one satellite) and 8 user outputs.

Can be used as a terminal (star topology) or as a cascade by using a simple switch.

Ref.	714303
Logical ref.	MS58CP
EAN13	8424450177136

Packing

Box	1 pcs.
-----	--------

Physical data

Net weight	379.00 g
Gross weight	379.00 g
Width	137.00 mm
Height	121.00 mm
Depth	29.00 mm
Main product weight	371.00 g

Highlights

- The passive terrestrial input provides compatibility with return channel applications such as CoaxData

- A switch for either powering terrestrial pre-amplifiers or allowing current circulation
- Can be powered directly from the satellite receiver, without the need for a power supply unit
- Passive terrestrial
- European design, quality, and manufacturing

Main features

- Very compact
- Made of zamak
- Input and output colour identification
- Available ECO mode
- Selector switch to shift between cascade and terminal modes
- 12 V power supply
- Low power consumption

Technical specifications : Ref. 714303

Number of inputs		5
Number of cascable outputs		5
Number of user outputs		8
Frequency range TERR.	MHz	47 ... 862
Frequency range SAT.	MHz	950 ... 2400
Input level TERR.	dB μ V	92
Input level SAT.	dB μ V	105
Through losses TERR.	dB	2
Through losses SAT.	dB	1.5 ... 4
Tap losses 1...8 TERR.	dB	26
Tap losses 1...8 SAT.	dB	1
Isolation H/V	dB	> 30
Isolation users	dB	> 25
Powering	Vdc	12
Max. current (PSU)	mA	5
Max. current (STB)	mA	35
Operating temperature	°C	-5 ... 45
Protection index		20