



NevoSwitch equipped with 5 QUAD inputs and 12 outputs

When quality matters

Cascadable and quad compatible multiswitch, equipped with 5 inputs (one terrestrial, and the four polarities of one satellite) and 12 user outputs. Can be used as a terminal (star topology) or as a cascade by using a simple switch.

Ref.	714404
Logical ref.	MS512NCQ
EAN13	8424450172872

Other features

Power Supply	12V - 0.8A
---------------------	------------

Packaging info

Box	1 pcs.
------------	--------

Physical data

Net weight	890.00 g
Gross volume	2.20 dm ³
Gross weight	890.00 g
Width	137.00 mm
Height	255.00 mm
Depth	29.00 mm
Main product weight	768.00 g

Highlights

- Very compact
- Made of zamak

- A 22 kHz tone can be generated, which makes it compatible with any LNB, including QUAD LNB.
- A switch for either powering terrestrial pre-amplifiers or allowing current circulation
- Remote power feeding using VL
- DC circulation from the inputs up
- Active terrestrial
- Available ECO mode
- Selector switch to shift between cascade and terminal modes
- 12 V power supply (Ref. 732101) included
- Low power consumption
- Input and output colour identification
- European design, quality, and manufacturing

Technical specifications : Ref. 714404

Number of inputs		5
Number of cascable outputs		5
Number of user outputs		12
Frequency range TERR.	MHz	47 ... 862
Frequency range SAT.	MHz	950 ... 2400
Input level TERR.	dBmV	0.092
Input level SAT.	dBmV	0.105
Through losses TERR.	dB	4
Through losses SAT.	dB	3 ... 8
Tap losses 1...8 TERR.	dB	2
Tap losses 1...8 SAT.	dB	1
Tap losses 9...16 TERR.	dB	4
Tap losses 9...16 SAT.	dB	2
Isolation H/V	dB	> 30
Isolation users	dB	> 25
Powering	Vdc	12
Max. current (PSU)	mA	85
Max. current (STB)	mA	35
Operating temperature	°F	23 ... 113
Protection index		20