



## NevoSwitch equipped with 5 QUAD inputs and 8 outputs

### When quality matters

Cascadable and quad-compatible multiswitch, equipped with 5 inputs (one terrestrial, and the four polarities of one satellite) and 8 user outputs. Can be used as a terminal (star topology) or as a cascade by using a simple switch.

Ref.	714413
Logical ref.	MSUK58NCQ
EAN13	8424450177891

### Other features

Power Supply	12V - 1.5A (UK plug)
--------------	----------------------

### Packaging info

Box	1 pcs.
-----	--------

### Physical data

Net weight	533.00 g
Gross volume	2.00 dm <sup>3</sup>
Gross weight	660.00 g
Width	137.00 mm
Height	121.00 mm
Depth	29.00 mm
Main product weight	365.00 g

### Highlights

- Very compact
- Made of zamak

- A 22 kHz tone can be generated, which makes it compatible with any LNB, including QUAD LNB.
- A switch for either powering terrestrial pre-amplifiers or allowing current circulation
- Remote power feeding using VL
- DC circulation from the inputs up
- Active terrestrial
- Available ECO mode
- Selector switch to shift between cascade and terminal modes
- 12 V power supply (Ref. 732101) included
- Low power consumption
- Input and output colour identification
- European design, quality, and manufacturing

## Technical specifications : Ref. 714413

Number of inputs		5
Number of cascable outputs		5
Number of user outputs		8
Frequency range TERR.	MHz	47 ... 862
Frequency range SAT.	MHz	950 ... 2400
Input level TERR.	dBmV	0.092
Input level SAT.	dBmV	0.105
Through losses TERR.	dB	2
Through losses SAT.	dB	1.5 ... 4
Tap losses 1...8 TERR.	dB	2
Tap losses 1...8 SAT.	dB	1
Isolation H/V	dB	> 30
Isolation users	dB	> 25
Powering	Vdc	12
Max. current (PSU)	mA	40
Max. current (STB)	mA	35
Operating temperature	°F	23 ... 113
Protection index		20