



## NevoSwitch equipped with 5 QUAD inputs and 8 outputs

When quality matters

Cascadable and quad-compatible multiswitch, equipped with 5 inputs (one terrestrial, and the four polarities of one satellite) and 8 user outputs.

Can be used as a terminal (star topology) or as a cascade by using a simple switch.

|              |               |
|--------------|---------------|
| Ref.         | 714413        |
| Logical ref. | MSUK58NCQ     |
| EAN13        | 8424450177891 |

### Other features

|              |                      |
|--------------|----------------------|
| Power Supply | 12V - 1.5A (UK plug) |
|--------------|----------------------|

### Packaging info

|     |        |
|-----|--------|
| Box | 1 pcs. |
|-----|--------|

### Physical data

|                     |                      |
|---------------------|----------------------|
| Net weight          | 533.00 g             |
| Gross volume        | 2.00 dm <sup>3</sup> |
| Gross weight        | 660.00 g             |
| Width               | 137.00 mm            |
| Height              | 121.00 mm            |
| Depth               | 29.00 mm             |
| Main product weight | 365.00 g             |

## Highlights

- Very compact
- Made of zamak
- A 22 kHz tone can be generated, which makes it compatible with any LNB, including QUAD LNB.
- A switch for either powering terrestrial pre-amplifiers or allowing current circulation
- Remote power feeding using VL
- DC circulation from the inputs up
- Active terrestrial
- Available ECO mode
- Selector switch to shift between cascade and terminal modes

- 12 V power supply (Ref. 732101) included
- Low power consumption
- Input and output colour identification
- European design, quality, and manufacturing

## Technical specifications : Ref. 714413

|                            |      |              |
|----------------------------|------|--------------|
| Number of inputs           |      | 5            |
| Number of cascable outputs |      | 5            |
| Number of user outputs     |      | 8            |
| Frequency range TERR.      | MHz  | 47 ... 862   |
| Frequency range SAT.       | MHz  | 950 ... 2400 |
| Input level TERR.          | dBmV | 0.092        |
| Input level SAT.           | dBmV | 0.105        |
| Through losses TERR.       | dB   | 2            |
| Through losses SAT.        | dB   | 1.5 ... 4    |
| Tap losses 1...8 TERR.     | dB   | 2            |
| Tap losses 1...8 SAT.      | dB   | 1            |
| Isolation H/V              | dB   | > 30         |
| Isolation users            | dB   | > 25         |
| Powering                   | Vdc  | 12           |
| Max. current (PSU)         | mA   | 40           |
| Max. current (STB)         | mA   | 35           |
| Operating temperature      | °F   | 23 ... 113   |
| Protection index           |      | 20           |