



NevoSwitch 9 inputs - 32 outputs

When quality matters

Multiswitch equipped with 9 inputs (one terrestrial and 8 for two satellites, each with its four polarities) and 32 user outputs.

Can be used as a terminal (star topology) or as a cascade by using a simple switch.

| | |
|---------------------|---------------|
| Ref. | 714605 |
| Logical ref. | MS932C |
| EAN13 | 8424450173114 |

Packing

| | |
|------------|--------|
| Box | 1 pcs. |
|------------|--------|

Physical data

| | |
|----------------------------|------------|
| Net weight | 2,447.00 g |
| Gross weight | 2,447.00 g |
| Width | 206.00 mm |
| Height | 515.00 mm |
| Depth | 29.00 mm |
| Main product weight | 2,435.00 g |

Highlights

- 10 dB Low Gain (LG) / High Gain (HG) switch for the attenuation of the satellite input signal for each 8-user group
- Remote power feeding using VL
- Current circulation between all inputs and cascades

- Compatible with return-channel applications
- European design, quality, and manufacturing

Main features

- Very compact
- Made of zamak
- Input and output colour identification
- Available ECO mode
- Selector switch to shift between cascade and terminal modes
- 12 V power supply
- Low power consumption

Technical specifications : Ref. 714605

| | | |
|----------------------------|------|--------------|
| Number of inputs | | 9 |
| Number of cascable outputs | | 9 |
| Number of user outputs | | 32 |
| Frequency range TERR. | MHz | 88 ... 862 |
| Frequency range SAT. | MHz | 950 ... 2400 |
| Input level TERR. | dBµV | 90 |
| Input level SAT. | dBµV | 112 |
| Through losses TERR. | dB | 8 |
| Through losses SAT. | dB | 8 ... 18 |
| Tap losses 1...8 TERR. | dB | 4 |
| Tap losses 1...8 SAT. | dB | 0 |
| Tap losses 9...16 TERR. | dB | 6 |
| Tap losses 9...16 SAT. | dB | 4 |
| Tap losses 17...24 TERR. | dB | 8 |
| Tap losses 17...24 SAT. | dB | 8 |
| Tap losses 25...32 TERR. | dB | 10 |
| Tap losses 25...32 SAT. | dB | 12 |
| Isolation H/V | dB | > 30 |
| Isolation users | dB | > 25 |
| Powering | Vdc | 12 |
| Max. current (PSU - LG) | mA | 170 |
| Max. current (PSU - HG) | mA | 355 |
| Max. current (STB) | mA | 35 |
| Operating temperature | °C | -5 ... 45 |
| Protection index | | 20 |