



1 terrestrial-2 satellite signal combiner 3 inputs: MATV-SAT-SAT

3-input combiner that combines a terrestrial signal with two satellite signals into two outputs.

Ref.	740710
Logical ref.	ESW201LTE
EAN13	8424450178003

Packaging info	
Box	1 pcs.
Carton	10 pcs.
Bucket	200 pcs.

Physical data	
Net weight	194.00 g
Gross volume	0.26 dm ³
Gross weight	194.00 g
Width	98.00 mm
Height	76.00 mm
Depth	27.00 mm
Main product weight	194.00 g

Highlights

- High-screening Zamak chassis
- Current pass from each of the outputs to each SAT input respectively, for LNB supply
- "F" connectors

Technical specifications : Ref. 740710

Connectors			"F" type
Number of inputs			3
Number of outputs			2
Frequency range	MHz	47 ... 790	950 ... 2400
IN (TERR) -> OUT attenuation	dB	5.5	> 30
IN (TERR) -> OUT A attenuation	dB	5.5	> 30
IN (TERR) -> OUT B attenuation	dB	5.5	> 30
IN (SAT) -> OUT attenuation	dB	> 28	1
IN (SAT A) -> OUT A attenuation	dB	> 28	1
IN (SAT B) -> OUT B attenuation	dB	> 28	1
Return losses (typ.)	dB	> 10	> 10
Operating temperature	°F		23 ... 113
Protection index (IP)			23