

Mixer för 1 x terrest och 2 x satellit 3 ingångar: MATV-SAT-SAT

3-ingångars mixer för att kombinera den terresta signalen med två satellitsignaler till dubbla utgångar.

Ref.	740710
	ESW201LTE
EAN13	8424450178003

Förpackning	
Låda	1 st.
Ask	10 st.
Hink	200 st.

Fysisk data	
Nettovikt	194,00 g
Bruttovolym	0,26 dm³
Bruttovikt	194,00 g
Bredd	98,00 mm
Höjd	76,00 mm
Djup	27,00 mm
Huvudproduktens vikt	194,00 g

Utmärkande egenskaper

- Zamak chassi för högsta HF-täthet
- Strömpass från respektive utgång till SAT-ingång för LNB-spänning.
- “F”-anslutning

Tekniska specifikationer

Ref. 740710

Connectors		"F" type	
Number of inputs		3	
Number of outputs		2	
Frequency range	MHz	47 ... 790	950 ... 2400
IN (TERR) -> OUT attenuation	dB	5,5	> 30
IN (TERR) -> OUT A attenuation	dB	5,5	> 30
IN (TERR) -> OUT B attenuation	dB	5,5	> 30
IN (SAT) -> OUT attenuation	dB	> 28	1
IN (SAT A) -> OUT A attenuation	dB	> 28	1
IN (SAT B) -> OUT B attenuation	dB	> 28	1
Return losses	dB	> 10	> 10
Operating temperature	°C	-5 ... 45	
Protection index (IP)		23	