



Wireless Managed Access Point WaveData Outdoor, 1xGbE WAN PoE

Your trusted Wi-Fi option for the busiest environments

Managed dual band Wi-Fi Access Point, specifically designed for outdoor installations. It provides a high-performance wireless mobility solution for deployments with medium/high density.

This Outdoor WaveData features an easy-to-install chassis that supports IP65, as well as 1 Gigabit Ethernet RJ-45 WAN (PoE) port and Wi-Fi (WLAN 802.11 b/g/n/ac, 2.4 and 5GHz).

Ref.	769011
Logical ref.	WAVEDATAPO
EAN13	8424450247532

Packaging info

Box	1 pcs.
------------	--------

Physical data


Net weight	1,950.00 g
Gross volume	10.50 dm ³
Gross weight	1,950.00 g
Width	245.00 mm
Height	475.00 mm
Depth	90.00 mm
Main product weight	1,950.00 g

Highlights


- 802.11ac Wave 2 managed access point
- Maximum aggregated throughput of 1.73Gbps
- MU-MIMO: Multi-User MIMO as defined in the 802.11ac standard that allows simultaneous multiple transmissions from the Access Points (AP) to up to four clients
- AP client isolation: It allows to isolate SSID AP clients and avoid STA to STA communication
- 4 dual band built-in antennas with high performance (4dBi) and beamforming
- Compatible with PoE 802.3af/at
- Up to 80MHz channel bandwidth
- Available remote management and monitoring of the entire WaveData network via the WaveBox (Ref. 769030)
- Maximum performance above 1Gb/s
- Operation in the 2,4 and 5GHz band
- Protection Index: IP65
- It withstands temperatures from -5 to 45°C
- 2.4GHz IEEE 802.11/b/g/n with 2 Streams MU-MIMO (2x2)
- 5GHz IEEE 802.11/n/ac Wave2 with 2 Streams MU-MIMO (2x2)
- Up to 16 SSIDs and 124 stations per SSID
- Support simultaneous dual band (2.4GHz and 5GHz) with band steering
- It implements fast roaming (IEEE 802.11r) between access points
- SNMP agent incorporated (Centralized management & monitoring)
- Wi-Fi schedule. Wi-Fi On/Off scheduling
- Automatic channel selection according to the spectrum conditions (for 2.4GHz and 5GHz)

Application example

WAVEDATA: OPTICAL FIBER NETWORK



WAVEDATA: DATA NETWORK (ETHERNET)



Technical specifications : Ref. 769011

Number of Gigabit Ethernet ports (10/100/1000BASE-T)		1
Wi-Fi standard		802.11 b/g/n (2x2) 2.4 GHz / 802.11 n/ac (2x2) 5 GHz
WiFi frequency band		2.4 GHz / 5 GHz
MIMO spatial streams		2x2 (2.4 GHz) / 2x2 (5 GHz)
2.4GHz Channel bandwidth		5MHz / 10MHz / 20MHz / 40MHz
5GHz Channel bandwidth		20MHz / 40MHz / 80MHz
Wi-Fi encryption		WPA
OFDM Modulations		16-QAM / 256-QAM / 64-QAM / BPSK / QPSK
Number of WiFi antennas		4
2.4GHz Antenna gain	dBi	6
5GHz Antenna gain	dBi	8
CPU number of cores		4
Core speed	MHz	716.8
RAM	MB	512
OS		Linux
PoE input		Yes
Max. power	W	7
Connector mounting		Wall / Ceiling
Operating temperature	°F	23 ... 113
Protection index (IP)		65