



Communications rack mounted and adjusted, 42RU, 800mmx800mm

19" Communications rack mounted and adjusted for Hospitality projects. This reference includes both the structure and the service of assembly and adjustment of the necessary equipment, as well as their connection to each other, in order to meet the requirements previously established with the client.

The elements included in the assembly are:

- VPN router
- Interconnection elements of the equipment included in the rack: patch-cords, panels, adapters, screws...
- FAN and temperature control devices
- Specific headends and service equipment required in the project (the number and type of devices must be previously defined in the capture of requirements with the client)
- Multiswitch with the number of inputs and outputs according to the project (optional)

Ref.	831303
Logical ref.	A-19RACK42
EAN13	8424450162804

Packaging info

Wooden box	1 pcs.
-------------------	--------

Physical data

Net weight	196,248.00 g
Gross volume	1,729.75 dm³
Gross weight	196,248.00 g
Width	800.00 mm
Height	2,010.00 mm
Depth	800.00 mm
Main product weight	116,000.00 g

Highlights

- Specifically intended for the distribution of Hospitality services, such as: IPTV, Interactive Television, VoD, nPVR...
- It includes a rack with steel frame and steel plates, equipped with four 19" sides, allowing the front and rear panels to move backwards
- It includes the devices and accessories required for the project (previously defined with the client), either GPON system or structured cabling system
- It includes the service of assembly and connection(*) of the equipment required in the project, as well as a complete testing, validation and optimization for correct operation
- Different equipment options depending on the project requirements
- The equipment is integrated into a single chassis for efficient management
- All the rack structural elements have punch-holes to facilitate ventilation
- Labelling of cabling and components included in the rack for easy maintenance

(*) Under this reference, only the cabling between the devices included within the rack is strictly included. Connection to the distribution network and any elements facilitating that connection (patch panels, brush strips, etc.) are not included. They may be included upon client request at an additional cost, provided there is space available in the rack.

Technical specifications : Ref. 831303

Modular spacing (standard)	in	19
Height	in	79.134
Width	in	31.496
Depth	in	31.496
Number of rack units (RU)		42
Material		Steel
Rack rail thickness	in	0.079
Color		Black
Surface finishing		Electrostatic powder
Number of doors		2
Front door material		Tempered glass
Rear door		Yes
Rear door material		Steel
Max. load capacity	kg	1000
Max. load capacity (with wheels)	kg	960
Max. load capacity (with legs)	kg	600
Removable sides		Yes
Installation type		Ground
Type of profile rail		L-shaped
Grounding		Yes
Protection index (IP)		20
Protection index (IK)		07