

Urban Maia Luminarie Z-Series 24LED 75W

Luminaires with a fresh style to enhance lighting in the heart of cities.

Decorative urban luminaire made of die-cast aluminium. The Urban Maia series has a compact design with smooth geometric lines, which integrates harmoniously with the environment, making it perfect for urban and residential spaces.
Urban Maia is designed with a lateral arrangement, perfect for areas that require a specific light distribution, such as streets, avenues, housing estates... With Urban Maia, perfect visual conditions are guaranteed, maintaining the quality of the night sky, while at the same time taking care of the aesthetics of the environment thanks to its modern and elegant style.
It stands out for its easy installation and maintenance without the need of tools. In addition, its high-quality tempered glass protector favours visual comfort and reduces glare.

The Z series offers maximum flexibility by incorporating a standard Zhaga Book 18 connector that enables Plug&Play connection with remote management nodes and facilitates sensor integration. It also offers CLO (Constant Lumen Output) regulation, NFC programming and 5-step multi-level pre-programmed dimming.
In addition, this open interface allows the Z series to be connected to remote management systems, combining the possibilities of full integration with additional sensors. It incorporates D4i-certified drivers and DALI2, Ready2Mains and U6Me2 communication protocols over the power line. Thus, our luminaires can be seamlessly integrated iinto Smart City projects project.

Ref.	66190400

Other features	
Number of LEDs	24
Lighting control	Remote control

Physical data	
Net weight	8,200.00 g
Gross volume	71.20 dm³

Power	75.00 W

Gross weight	9,900.00 g
Width	516.00 mm
Height	208.00 mm
Depth	617.00 mm
Main product weight	8,200.00 g

Packaging info	
Box	1 pcs.

Highlights

- **Design and quality:** die-cast aluminium body with high quality tempered glass closure and compact and stylish design with geometric lines
- **100% electrical safety:** Class II with no need for grounding and SELV certified
- **Quick and tool-free maintenance:** with electrical disconnection on opening
- **Energy saving:** long maintenance-free service life, which increases savings compared to other technologies, achieving savings of up to 80%
- **Supports the quality of the night sky:** in accordance with the IAC (Instituto de Astrofísica de Canarias) requirements, the luminaire is suitable for areas of special protection against light pollution (flux emission to the upper hemisphere < 0.1%)
- **Quality guarantee:** technology designed and manufactured in our state-of-the-art facilities, in collaboration with national and local providers, ensuring total control, with accurate traceability and rigorous verification of all processes

Discover

Our ranges of luminaires encompass a wide range of powers and number of LEDs, in addition to being customizable in the types of lighting control, colour temperatures, optics and their light distribution, and finishes. **A product can be configured according to these parameters, and ordered by its numerical or logical reference**, as follows:

Selecting the luminaire by the numerical reference:

This is a numerical code made up of 14 digits:

- The first 6 digits represent a code that depends on the Series of the luminaire, the number of LEDs and the power
- The next 8 digits allow you to choose the configurable parameters of the luminaire: lighting control, colour temperature, type of optics and finish

Series		Dimming		Colour Temperature		Optics		Finish	
631703	*Urban Alameda E 24LED 53W*	**00**	*No Dimming*	**18**	*PC Amber*	**02**	*SP*	**02**	*Black*
631713	*Urban Alameda E 24LED 39W*	**01**	*Dimming*	**22**	*2200K*	**11**	*D90*	**xx**	*Custom*
				27	*2700K*	**17**	*T2-C90*		

Light distribution curve

Light distribution curve

Light distribution curve

Light distribution curve

Light distribution curve

Light distribution curve

Light distribution curve

Light distribution curve

Light distribution curve

Features



Fresh, rust-free design that lasts over time

The Urban Maia luminaire consists of a circular die-cast aluminium body with a modern and stylish design that blends perfectly into urban and residential environments.
Its high quality tempered glass enclosure improves visual comfort and reduces glare, providing the appropriate amount of light for each situation.

On the other hand, the quality is shown in the luminaire's high durability. Thanks to the 6063 T5 aluminium heatsink, which ensures excellent thermal management of the LED modules, the luminaire's service life is extended and efficiency is improved.



Quick and tool-free maintenance

The Urban Maia series features an optimised design to allow any maintenance task to be carried out quickly and without the need of tools. The casing includes a locking system to fix the cover of the luminaire, making easier the replacement on site of its components. In addition, its light weight makes it easy to handle during installation and manipulation of the luminaire.



Maximum security

The Urban Maia luminaire has the highest levels of electrical protection: its Class II guarantees safety without the need for grounding thanks to the double isolation of the components. Furthermore, the SELV certificate provides an output voltage of less than 60V, minimising the risk of electrocution in the case of system failure. In addition, its driver, optical group and IP67 connections offer integral protection to all optical and electronic elements against water and dust ingress, eliminating any effect caused by external agents.

In addition, Urban Maia includes an automatic disconnection system, which shuts off the electric current when the luminaire is opened. This avoids the risk of electrocution when manipulating the luminaire.



A world of possibilities

Each situation requires specific lighting features, that's why our luminaires offer multiple alternatives to meet the needs of each context:

- A wide selection of highly homogeneous colour temperatures (SDCM<3): PC Amber, 2,200, 2,700, 3,000 and 4,000ºK
- 9 different types of optics are available to achieve lighting adapted to any environment: P, ME, T2, T3, T4, APZ, SCL, PX and PXL
- Variety of finishes in any colour of the RAL range
- CRI>70 and available on request CRI>0 and CRI>90

And if you don't find what you are looking for, we have even more options available on request. We are pleased to study your project in a tailored, non-binding way. Contact us, and we will help you choose the perfect lighting.



Control and connectivity

This range is equipped with D4i (Digital Illumination Interface Alliance) certified drivers, which have the ability to store luminaire data. At the same time, D4i defines how to feed from the driver to other DALI2 devices connected through the bus, simplifying communication with sensors.
All Z Series luminaires are DALI2 and CLO dimmable and include the standard Zhaga Book 18 socket, which allows Plug&Play connection with remote management nodes and the integration of multiple sensors (presence, twilight, noise, air quality...).



Televes quality guarantee

Our cutting-edge facilities are equipped with all the means to guarantee a quality and reliable luminaire, highlighting precise traceability and rigorous verification of all processes. This is possible thanks to an advanced methodology of product design under simulation and in-house manufacturing on robotised lines, in collaboration with national and local providers.

Mounting details

Tool-free top opening for access to electronics and LED module. Electrical disconnection on opening to minimise the risk of electrocution.

Assembly is quick and easy by means of a strong, durable and unique accessory for vertical and horizontal installation. The position gradation can be adjusted up to 90º.
It is adaptable to poles, columns and arms from Ø 42 to 60 mm, adapters for other tube diameters are available.


90°
45°
0°
-45°
-90°
-90° ... 90°

Technical specifications

Ref. 66190400

Number of leds		24													
Power	W	75													
Pre-programmed dimming		Yes													
Control interface		Dali 2													
Node/sensor connection type		1x Zhaga													
Optic type options		P		T2		T3		T4		ME		APZ		PX	SCL
Lens type		PC lens		PC lens		PC lens		PC lens		PC lens		PC lens		PMMA lens	PC lens
Color temperature options		2200K			2700K			3000K				4000K			PC Amber
Luminous flux	lm	8025			8775			9150				9750			3750
Lighting efficiency	lm/W	107			117			122				130			50
LED current	mA	500			500			500				500			1000
Duration	h	100000													
Working life		L90B10													
Constant ligh output (CLO)		Yes													
Standard Deviation Colour Matching (SDCM)		< 3													
Color rendering index (CRI)		70													
CE Mark		Yes													
ENEC Certificate		No													
Protection Class IEC		Class II													
EU RoHS Compliant		Yes													
IK Rating (light module)		8													
IK Rating (whole luminaire)		8													
IP Rating (light module)		66													
IP Rating (whole luminaire)		66													
Color		Black													
Material		Aluminium													
Material cover		Transparent plastic													
Fixation Material		Aluminium													
Mast diameter Max	in	2.362													
Mast diameter Min	in	1.654													
Mounting method		Post top/side entry													
Surface protection		Powder coating													
Surface facing the wind	m^2	0.211													
Number of LED modules		2													
Minimum power factor		0.9500													
Lighting source type		LED													
Replaceable light source		Yes													
Cable		Yes													
Power consumption tolerance	%	5													
Lighting flux tolerance	%	8													
Electric connection		3-pole waterproof connector													
Inrush current	A	54													
Input voltage	Vac	220 ... 240													
Mains frequency		50 Hz													
Max. Operating temperature	°F	104													
Min. Operating temperature	°F	-31													