




FK8 Multi-fiber Cable Single-Mode 8 fibers, Cca Euroclass and UV- resistant LSFH, indoor/outdoor, with rodent protection

8-fiber cable, each with a different color, and UV-resistant LSFH jacket, for indoor and outdoor installation. This improves organization and facilitates identification.

It features a rodent-resistant finish using fiberglass yarns integrated into the sheath, which act as a deterrent by being uncomfortable for rodents, preventing them from biting the cable without damaging the fiber. This protection method offers the following advantages compared to metallic protection:

- As it is a non-metallic material, it does not rust, providing greater resistance to degradation caused by corrosion.
- It is a dielectric protection, preventing the transmission of electrical energy through it and thus avoiding the issues associated with it.
- It is a lighter material, significantly reducing weight during transport and installation.

In addition, unlike chemical rodent protection, it does not produce smoke in case of fire.

These fiberglass yarns also act as structural reinforcement, providing high tensile strength during installation.

Includes water-blocking gel in each micromodule, providing a physical barrier that prevents water

from spreading inside the cable. This prevents changes in the optical refractive index and avoids ice formation in freezing environments, reducing damage caused by moisture freezing. The reference 231824 is supplied per metre.

Ref.	231825
Logical ref.	OSK8-2000NGT
EAN13	8424450329436

Other features

Colour	Orange
Length	2.00 km

Packaging info

Reel	2000 m
-------------	--------

Physical data

Net weight	48.00 g
Gross volume	0.13 dm ³
Gross weight	48.00 g
Width	8.00 mm
Height	1,000.00 mm
Depth	8.00 mm
Main product weight	48.00 g

Highlights

- Cca-s2,d2,a1 Euroclass
- Low attenuation
- Organized in fiber micro-modules
- Blocking jelly in each micro-module, offering great protection against water
- Micro-modules protected with water-blocking yarns, providing enhanced resistance against moisture ingress
- Rodent protection fibres, to prevent damage to the optical fibres caused by rodent attack

- Good structure reinforcement using fiberglass, which allows to maintain its traction without the need for a central guiding wire for resistance
- 9/125, ITU-T G.657.A2 fiber type
- UV-resistant LSFH sheath, orange colour

Technical specifications : Ref. 231825

Euroclass			Cca
Euroclass: Smoke Production			s2
Euroclass: Flaming droplets			d2
Euroclass: Acidity			a1
Fiber core type			Single-mode (ITU-T-G.657.A2)
Fiber core diameter	µm		9
Fiber cladding diameter	µm		125
Coating buffer diameter	µm		250
Cable structure			Tight buffer
Plastic buffer diameter	in		0.033
Outer sheath Diameter	in		0.28
Outer sheath Material			LSFH, UV-resistant
Blocking jelly			Yes
Optical fiber attenuation: 1310nm	dB/km		< 0.4
Optical fiber attenuation: 1550nm	dB/km		< 0.3
Long tension	N		1000
Structure reinforcement element			Glass Yarns
Rodent protection			Glass Yarns
Short crush (@100mm)	N		1000
Long crush (@100mm)	N		750
Minimum bending radius	in		27.953
Operating temperature	°F		-40 ... 158